



Metric table

Dimensions in: millimeters - inches

d₀ Coupling Ø GN 2240 / GN 2241	d₁	b	Number of teeth
14 0.55	14 0.55	6 0.24	4
20 0.79	20 0.79	8 0.31	4
30 1.18	30 1.18	10 0.39	4
40 1.57	40 1.57	12 0.47	6
55 2.17	55 2.17	14 0.55	8

Specification

- Thermoplastic Polyurethane (TPU)
Temperature resistant up to 140 °F (60 °C)
- Hardness
- 80 shore A, blue
- 92 shore A, white
- 98 shore A, red
- [Elastomer Characteristics](#) → page QVX
- [RoHS compliant](#)



BS
WS
RS

Information

Coupling spiders GN 2240.1 are intended as replacement parts or for adjusting GN 2240 / GN 2241 elastomer jaw couplings.

The choice of three coupling spiders with different hardness values allows the properties of the coupling to be optimally matched to the specific requirements.

see also...

- [Elastomer Jaw Couplings GN 2240 \(with Clamping Hub\)](#) → page QVX
- [Elastomer Jaw Couplings GN 2241 \(with Grub Screw\)](#) → page QVX

<p>How to order</p> <p>GN 2240.1-14-BS</p>	1	Diameter d ₁
	2	Hardness