

## NOTES:

MATERIAL: HOUSING: THERMOPLASTIC POLYESTER, UL94V-0 STEEL, TIN PLATED SHELL: CONTACT: COPPER ALLOY, GOLD FLASH PLATED **OPERATING TEMPERATURE:** 

.X ±0.25 .XX ±0.13

.XXX ±0.05

10.70

5.80

-55°C ~ 125°C


5000MΩ min.

1000V AC rms

POWER/CO-AX CONTACT RATING: 10A (CURRENT)

(IF PRESENT) SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:



	SW REFERENCE NO.: 630 COMBO ASSEMBLY			
COMBINATION	DRAWN: C.B	DATE: JAN. 01/20	19	
	CHECKED:	DATE:		
EDAC INC	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
YOUR CONNECTION TO QUALITY & SERVICE	SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWING NUMBER: 630-3WK3240-1TC		ISSUE
		PART NUMBER: 630-3WK	3240-1TC	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

REFERENCE NO .:	630 C	OMBO AS	SSEME	BLY	
AWN: C.B		DATE:	JAN.	01/201	9
ECKED:		DATE:			
		0		0.5	

