HellermannTyton

Specification Sheet

Part Number: MCRFW-ENT



InfoStream Multi-Channel Raceway Entrance End Fitting, PVC, Office White, 1/pkg

Article Number	250-00017
Туре	MCR-ENT
Color	Office White (OEWH)
Features & Benefits	 Raceway and fittings are manufactured from a UL94 V0 rated material to insure compliance with codes. All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard. Raceway and fittings are UL Listed to 600 Volts to meet new UL5A and CSA 22.2 No. 62-93 standards.
Quantity Per	bag
Product Description	For use as a ceiling drop, conduit transition from end or base of raceway, or low voltage entrance from end or base of raceway. Includes dual 0.75", 1.0", 1.25", 1.75", 2.0" and 2.5" knockouts.

Short Description	InfoStream Multi-Channel Raceway Entrance End Fitting, PVC, Office White, 1/pkg
Global Part Name	MCR-ENT-PVC-WH
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 V0
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)
Reach Complaint(Article 33)	No
ROHS Complaint	Yes
UL Listed (US and Canada)	Yes
UL Listed (US	Yes
Package Quantity(Imperial)	1
Package Quantity (Metric)	1
Customs Number	3925900000

© 2019 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions