



1





THIS SERIES FULLY CONFORMS TO

THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

±0.13				
±0.05				
	10.70			
	5.80			_
			<b>m</b> -	_
		$\square$	╢	h .
			116-	11

9.40

2.54


.XX

.XXX



MATERIAL: HOUSING: SHELL: CONTACT:	THERMOPLASTIC POLYEST STEEL, TIN PLATED COPPER ALLOY, GOLD FLA	
OPERATING TEMPERATURE:	-55°C ~ 125°C	
POWER/CO-AX CONTACT RATING: (IF PRESENT)	20A (CURRENT)	
SIGNAL CONTACT CURRENT RATING: SIGNAL CONTACT RESISTANCE:	5A PER CONTACT 10mΩ MAX.	
INSULATOR RESISTANCE:	5000MΩ min.	
DIELECTRIC		
WITHSTANDING VOLTAGE:	1000V AC rms	

		SW REFERENCE NO.: 630 COMBO ASSEMBLY			
	COMBINATION	DRAWN: C.B	DATE: JAN. 01/2019		
				DATE:	
	EDAC INC TORONTO, ONTARIO CANADA	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	2
			DRAWING NUMBER: 630-5W1-250-2TC		ISSUE
	YOUR CONNECTION TO QUALITY & SERVICE		PART NUMBER: 630-5W1	-250-2TC	1



HS

COMPLIANT

П

