CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Sounector dimension -Shell Material : Aluminium -Shell Plating : Olive drab Cadmium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer	י ר ת ב ב ביינו ביינו ביינ			0	σ	A		7
CARACTERISTIC Standard: Baced on MUCTURSP99 Saries BI Shell Natorial ::::::::::::::::::::::::::::::::::::	4							4
Starter				LAYOUT SHO	WN AS EXAMPLE			3
CHARACTERISTIC Standard : Based on MIL DTL 38999 Series III Shell Material :: And Material :: Aduntinium Shell Material :: Shell Shell :								
Standard : Based on MIL-DTL-38999 Series III Shell Material : Aluminium Shell Material : Aluminium Shell Material : Compare Many Seals & Grommet : Slicon Elastomer - Contact Mating : Gold over copper Alloy 08 Jum minimum - Ourbach Mating cycles : Ourbach Mating cycles - Oelivered with Souriau contacts and Accessories : Ourbach Material - Temperature Range : - 65°C to +175°C - Sail Spray : 500 hours BASIC SERIES: : 80 Souriau Lister: : 17 V 22 SHELL TYPE : I Mag with AFI Shielding : 17 VITHE Contact Type: : Standard Crimp Contact Sitter is : W = Olive drab Cadmium : Contact Type: : Socket(St00 Mating) ORIENTATION : IN : Contact Type: : Socket(St00 Mating) Outbact Type: : Stocket(St00 Mating) : Contact Type: : Socket(St00 Mating) Outbact Type: : Stocket(St00 Mating) : Contact Type: : : Stocket(St00 Mating) </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
Shell Material : Aluminium Shell Material : Aluminium Shell Material : Aluminium -Shell Plaing : Olive drab Cadmium -insulator : Thermoplastic -Contact : Since Cooper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plaing : Gold over cooper Alloy 0.8µm minimum -Durability : Sold Mating cycles -Delivered with Sourciau contacts and Accessories : -Temperature Range : 657 to +173°C -Sail Spray : Sold hours BASIC SERIES: : BD BASIC SERIES: : BD BASIC SERIES: : Sold hours 22 B ORIENTATION: IN : ORIENTATION: IN ORIENTATION: IN : CONTACT TYPE: SockTigon Matings) ORIENTATION: IN : CONTACT TYPE: SockTigon Matings) PLTING : W = Olive drab Cadmium	Connector							
-Shell Plating : Olive drab Cadmium -Shell Plating : Olive drab Cadmium -Insulator : Thermoplastic -Contact S : Copper Alloy -Seals & Grommet : Silicon Elistomer -Contact Plating : Gold over copper Alloy -Seals & Grommet : Silicon Elistomer -Outsch Plating : Gold over copper Alloy -Seals & Grommet : Silicon Elistomer -Outsch Plating : Gold over copper Alloy 0.8µm minimum -Durability : Solicon Elistomer -Satt Spray : Solicon Elistomer Shell TYPE : Plug with RFI Shielding Contact Type: : Solicon Elistomer Solicit String : Contact Type: Solicit String	-Shell Material Aluminium	35.7 Max						\vdash
Insulator :: Thermoplastic -Contacts :: Copper Alloy -Seals & Grommet :: Silicon Elastomer -Contact Plating :: Sold over copper Alloy 0.8µm minimum -Durability :: Sol Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range :: -65°C to ±175°C -Sait S pray :: 500 hours - BASIC SERIES:: 80 5 127 W 22 8 N Not Distance : Souriau contact in and in the reproduced of Souriau contact Type :: Standard Crimp Contact SHELL SIZE :: 17 PLATING :: W = Olive drab Cadmium 127 W 22 8 N Not Distance : Souriau contact in and the reproduced of Souriau contact in the property of SOURIAU Souriau contacts in the property of SOURIAU Souriau contact in the property of Souriau contact with the preproduced of communicated without pering of Souriau contact in the property of Souriau co								
-Contacts :: Copper Alloy -Seals & Grommet :: Silicon Elastomer -Soutact Plating :: Sold over copper Alloy 0.8µm minimum -Durability :: Sold over copper Alloy 0.8µm minimum -Delevered with Souriau contacts and Accessories PN: 8D517W22BN -sait Spray :: Sold over copper Alloy BASIC SERIES: 80 5 SHELL TYPE : Standard Crimp Contact SHELL SZE : 17 CONTACT TYPE :: SockET(500 Matings) CONTACT TYPE :: Standard Crimp Contact CONTACT TYPE :: SockET(500 Matings) SHELL SZE : 17 CONTACT TYPE :: SockET(500 Matings) PLATING :: W = Olive drab Cadmium CONTACT TYPE :: SockET(500 Matings) CONTACT TYPE :: SockET(500 Matings) : PLATING :: W = Olive drab Cadmium CONTACT TYPE :: SockET(500 Matings)			the Specifications issued by either of the Parties or by a third party					
-Contact Plating :: Gold over copper Alloy 0.8µm minimum -Durability :: S00 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range :- 6:5°C to +175°C Salt Spray :: S00 hours A 17-10-2016 First Release	-Contacts : Copper Alloy			(protessional recor	nmendation, technical no	tice.)		
-Durability :: 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range :-65°C to +175°C -Sait Spray :: 500 hours BASIC SERIES: 8D SHELL TYPE : Standard Crimp Contact ORIENTATION : N CONTACT TYPE SHELL SIZE : 17 CONTACT TYPE PLATING W 20 of weat CONTACT TYPE SOURIAU WWW.SOURIAU.COM Totation of weat SUBURIAU PLATING W : SOURIAU DRG N° SUBS17W22BN-C : 1/2								
-Delivered with Souriau contacts and Accessories -Temperature Range :-65°C to +175°C -Salt Spray : 500 hours A 17-10-2016 First Release MOD N° Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 5 17 W 22 B N SHELL TYPE :Plug with RFI Shielding ORIENTATION :N NA 2 859 CONTACT TYPE :Standard Crimp Contact SUBIAL It must not be erponerly of communicated without permission SHELL SIZE : 17 CONTACT TYPE : Standard Crimp Contact SUBIALU WWW.SOURIAU.COM This document is the property of communicated without permission PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(SOO Matings) CONTACT LAYOUT : 17-22 SOURIAU SOURIAU DRG N° SHEET A3 SDS17W22BN-C 1/2					FR	Not Listed		2
- Jenered with Journal Contact Sand Accessories - Temperature Range :65°C to +175°C - Salt Spray : : 500 hours - Time - Latest modification - by MOD N [*] - Designed By: Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING - Designed By: Date: CUSTOMER DRAWING - Designed By: Date: CUSTOMER DRAWING - Designed By: Date: SCALE - SHELL TYPE : Plug with RFI Shielding - CONTACT TYPE : Standard Crimp Contact - SHELL SIZE : 17 - Designed Crimp Contact - SHELL SIZE : 17 - Designed Crimp Contact - SUBAD - CONTACT TYPE : SOCKET (500 Matings) -			PN: 8D517W22BN					
-Salt Spray : 500 hours -Salt Spray : 500 hours A 17-10-2016 First Release ISS DATE Latest modification - by MOD N* Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D SHELL TYPE: Plug with RFI Shielding CONTACT TYPE: Standard Crimp Contact SHELL SIZE: 17 V 22 BASIC SERIES: 8D SHELL SIZE: 17 V 22 CONTACT TYPE: Standard Crimp Contact SHELL SIZE: 17 V CONTACT TYPE: SOURIAU WWW.SOURIAU.COM It must not be reproduced or communicated without permission CONTACT TYPE: SOURIAU DRG N° SOURIAU SOURIAU DRG N° MAT SOURIAU DRG N° SUBS 17/W22BN-C 1/2								
ISS DATE Latest modification - by MOD N* Designed By: Date: CUSTOMER DRAWING BASIC SERIES: 8D 5 - 17 W 22 B N SHELL TYPE : Plug with RFI Shielding ORIENTATION : N ORIENTATION : N SOURIAU General linear NPRDS / PROJECT SHELL SIZE : 17 ORIENTATION : N CONTACT TYPE : SOCKET(500 Matings) SOURIAU WWW.SOURIAU.COM SOURIAU FORMAT SOURIAU DRG N° SHEET A3 8D517W22BN-C SHEET			A 17-10-2016 Fi	rst Release				
BASIC SERIES: 8D 5 17 W 22 B N SHELL TYPE : Plug with RFI Shielding Status Status </td <td></td> <td></td> <td>ISS DATE</td> <td>Latest modification - by</td> <td></td> <td></td> <td>MOD N°</td> <td>,</td>			ISS DATE	Latest modification - by			MOD N°	,
BASIC SERIES: 8D 5 - 17 W 22 B N SCALE Tolerances: Tolerances: 859 SHELL TYPE : Standard Crimp Contact ORIENTATION : N NA WWW.SOURIAU.COM This document is the property of SOURIAU SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) WWW.SOURIAU.COM This document is the property of SOURIAU PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 17-22 FORMAT SOURIAU DRG N° SHEET A3 8D517W22BN-C 1/2		De	esigned By:	Date:		CUSTOMER DRAWING		_
BASIC SERIES. BD S I IV V ZZ B N SHELL TYPE Plag with RFI Shielding IV V ZZ B N IV			TITLE Aluminium Plug 8D series					
CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SOURIAU This document is the property of SOURIAU.COM SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) CONTACT TYPE : SOCKET(500 Matings) SOURIAU It must not be reproduced or communicated without permission PLATING : W = Olive drab Cadmium CONTACT TYPE : SOCKET(500 Matings) FORMAT SOURIAU DRG N° communicated without permission Image: Note of the source of the so				— – – – (- 🕀 – – Toler	ances:			
SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) SOURIAU it must not be reproduced or communicated without permission PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 17-22 FORMAT SOURIAU DRG N° SHEET A3 8D517W22BN-C 1/2							operty of	_ 1
PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 17-22 FORMAT SOURIAU DRG N° SHEET A3 8D517W22BN-C 1/2		3	SOURIAU	WWW.SOUR	IAU.COM	it must not be reprodu		
A3 SOORIAO DIGIN 1/2			FORMAT	(<u>)</u>				_
		CONTACT LATOOT . 17-22						
						•		

	工	۵	г	m		0
4		Contact Layout 22				
 ა	Ctc A B C D	2#12 2#8 Triax 17-22 X Y 0 4.57 6.32 0 0 -4.57 -6.32 0				
	-					SOURIAU shall not be liable for ar due to a use of the Products w the Specifications issued by either o (professional recommenda
2						PN: 8D517
					A 17-10-20 ISS DATE Designed By: TITLE	16 First Release Latest modification - by Date: Alumin
-					SCALE NA SOURIA	General linear Tolerances: ±
	Н	G	F	E	FORMAT A3 D	SOURIAL 8D517W

