<u> ۲</u> (۵)	m m		0	₿ >	
	ØS			WPLE	
	Keying Shown as example				
CHARACTERISTICS-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Composite-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy	Connector dimensionDimNominalØS41.7 MaxZ'31.5 MaxVV THREADM31x1-6g		SOURIAU shall not be liable for any n due to a use of the Products which the Specifications issued by either of th (professional recommendation	does not comply with e Parties or by a third party	
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles			Country FR	Jurisdiction & Control List Not Listed	
-Delivered without Souriau contacts			PN: 8D521M4	8PEL	
-Temperature Range: -65°C to +200°C-Salt Spray: 2000 hours-Mass: 29.3 g ± 10%		A 08-10-201 ISS DATE Designed By:	L6 First Release Latest modification - by Date:	CUSTOMER DRAWING	MOD N°
		TITLE	Composi	te Plug 8D series	
BASIC SERIES: 8D 5 - 21 N SHELL TYPE : Plug with RFI Shielding	Delivered W/C		General linear Tolerances: ±	M NPRDS / PROJECT 859 This document is the pr SOURIAU it must not be reprod communicated without p	uced or
PLATING : M = Nickel	CONTACT LAYO	JT : 21-48 FORMAT A3	SOURIAU D 8D521M48		SHEET 1/2
H G	F E	D		B A	

	т	۵	н г	m	D	0	
		Contact Layout					
4	×						

F

Е

G

Н

4#8 Power

	21-48				
Ctc	х	Y			
Α	4.57	4.57			
В	4.57	-4.57			
С	-4.57	-4.57			
D	-4.57	4.57			

ယ

 \sim

due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country FR PN: 8D521M48PEL 08-10-2016 First Release А DATE Latest modification - by ISS Designed By: Date: TITLE SCALE General linear (\oplus) Tolerances: NA ±---**SOURIAU** WWW.SOURIAU.COM FORMAT A3 С D

