

EnviroSense2 (E2) Environmental Sensor Module with Temperature and Digital Inputs

MODEL NUMBER: E2MTDI



Monitors ambient temperature conditions, as well as contact closures from alarm, security and telecom products.

Description

The E2MTDI E2 Environmental Sensor Module works with Tripp Lite LX Platform devices, including WEBCARDLX, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs. By connecting the included USB cable to an LX Platform device, the E2MTDI allows you to remotely monitor ambient temperature conditions in network environments. It also monitors, via dry contact interface, contact closure status of two compatible products, such as smoke detectors, fire alarms and security systems.

If temperature values exceed a certain limit or monitored contacts change state, it is recorded in the event log of the LX Platform device's PowerAlert® Device Manager interface. The E2MTDI mounts magnetically to most racks and cabinets. Up to three E2 modules can be daisy-chained together. A built-in retention harness secures cable connections to reduce clutter.

Features

Compatible with Tripp Lite LX Platform Devices

- Compatible devices include WEBCARDLX, WEBCARDLXS, PDU3XE-Series PDUs and PDU3E-Series PDUs
- Measures and monitors ambient temperature
- Monitors contact closure status of alarm, security and telecom products
- Only dry contact open/closed connection allowed

Easy to Install and Operate

- Attaches magnetically to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together
- Built-in cable harness reduces clutter

Highlights

- Compatible with Tripp Lite LX Platform devices
- Easy magnetic mounting to most racks and cabinets
- Up to 3 E2 modules can be daisy-chained together
- Built-in cable harness reduces clutter
- USB cable included

Package Includes

- E2MTDI EnviroSense2 Environmental Sensor Module
- USB cable (A/Micro-B), 3 ft.
- Owner's manual

- USB cable included
- Compatible with Tripp Lite's free downloadable PowerAlert software

Specifications

OVERVIEW	
UPC Code	037332196255
PHYSICAL	
Cable Length (ft.)	3
Cable Length (m)	0.91
Shipping Dimensions (hwd / in.)	1.10 x 4.30 x 6.00
Shipping Dimensions (hwd / cm)	2.79 x 10.92 x 15.24
Shipping Weight (lbs.)	0.29
Shipping Weight (kg)	0.13
CONNECTIONS	
Side A - Connector 1	USB A (FEMALE)
Side B - Connector 1	MICRO-USB B (FEMALE)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	2-year limited warranty