



Siemens Low Voltage Circuit Protection Heavy Duty Safety Switches. Type: ENCLOSED, SAFETY SWITCH Std: UL V. Rating: 120/240V A. Rating: 100A Wattage: 3W No. Of Poles: 2P F. Rating: 60Hz Action: SINGLE THROW Material: 304SS Enclosure: TYPE 3R. 2-3 point mounting holes. O. Cycles: 10000 O. Temperature: (-20F-120F) AMBIENT TEMPERATURE Environmental Conditions: OUTDOOR

| | |
|--|-------------------------------------|
| mechanical service life (switching cycles) typical | 10000 |
| fastening method | SURFACE |
| number of poles | 2 |
| suitability for operation | LOAD TRANSFER BETWEEN POWER SOURCES |
| Electricity | |
| ampacity | 100 A |
| supply voltage frequency rated value 50/60 Hz | Yes |
| Model | |
| product brand name | SIEMENS |
| product type designation | DOUBLE THROW PLUG FUSE |
| type of electrical connection | MECHANICAL LUGS |
| Mechanical Design | |
| design of the housing | TYPE 3R |
| design of the actuating element | DOUBLE THROW |
| material | STEEL |
| General product approval | |
| certificate of suitability | UL98 |

last modified:

9/16/2021 

