TRIDONIC

Driver LCO 96W 700/1050/1400/2000/2670mA 0-10V C ADV UNV

OUTDOOR advanced series



Product description

- _ Constant current LED driver
- _ Only for US applications
- _ Dimmable via 0 ... 10 V interface
- $_$ Dimming range 10 to 100 %
- _ UL Listed Class P
- _ FCC Part 15
- _ Dry and damp location
- _ Max. output power 96 W
- _ Up to 92 % efficiency
- _ Nominal lifetime up to 100,000 h
- _ 5 years guarantee (conditions at <u>www.tridonic.com</u>)

Housing properties

- _ Metal casing black
- _ Potted style
- _ Type of protection IP67

Functions

- _ Over voltage protection
- _ Short-circuit protection
- _ No-load protection

Typical applications

_ For cobra head, high bay and street applications

Website http://www.tridonic.us/28002164





 Spotlights
 Downlights
 Linear
 Area
 Floor | Wall
 Free-standing
 Street
 Decorative


Article information 06/23 Subject to change without notice.

TRIDONIC

Driver LCO 96W 700/1050/1400/2000/2670mA 0-10V C ADV UNV

OUTDOOR advanced series

The complete data sheet for this product is available in the Downloads section.



Dimensions in mm / inch

Approval marks

RoHS

Standards

UL 8750, UL 1310, FCC PART 15, ANSI C62.41, ANSI C63.4, UL 1012, NEMA 4, CSA C22.2