CUI DEVICES

late 06/25/2021

page 1 of 3

MODEL: HSS03-B20-P318 | DESCRIPTION: HEAT SINK

FEATURES

- TO-220 package
- solder pin
- aluminum alloy
- black anodized finish





thermal resistance¹ power dissipation1 @ 75°C ∆T, @ 75°C ∆T, @ 1 W, @ 1 W, @ 1 W, 400 LFM 200 LFM nat conv nat conv nat conv (°C/W) (°C/W) (°C/W) (°C/W) (W) 16.9 5.6 4.5 5.49 HSS03-B20-P318 13.67


Note: 1. See performance curves for full thermal resistance details.

PERFORMANCE CURVES

	Heatsink Temperature Rise Above Ambient ($\Delta T = Ths - Ta$) (°C)		
Power (W)	Natural Conv.	200 LFM	400 LFM
0	0	0	0
1	16.9	5.6	4.5
2	31.9	11.4	8.6
3	45.1	17.0	12.8
4	57.8	22.8	17.0
5	69.6	28.3	20.9
6	80.8	34.1	25.1
7	92.0	39.4	29.3
8	102.5	45.3	33.6
9	113.4	50.9	37.8
10	123.7	56.8	42.0
8	102.5 113.4 123.7	45.3 50.9	33.6 37.8 42.0

Ths: "hot spot" temperature measured on the heatsink


Ta: ambient temperature



MECHANICAL DRAWING

units: mm tolerance: ±0.3 mm

MATERIAL	AL 1050
FINISH	black anodized
THICKNESS	1.2 mm
PIN MATERIAL	phosphor bronze
PIN PLATING	2∼3 µm tin
WEIGHT	7.6 g



Additional Resources: Product Page

CUI Devices | MODEL: HSS03-B20-P318 | DESCRIPTION: HEAT SINK date 06/25/2021 | page 3 of 3

REVISION HISTORY

rev.	description	date
1.0	initial release	06/25/2021

The revision history provided is for informational purposes only and is believed to be accurate.

CUI DEVICES

CUI Devices offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI Devices reserves the right to make changes to the product at any time without notice. Information provided by CUI Devices is believed to be accurate and reliable. However, no responsibility is assumed by CUI Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI Devices products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.