

Specification Sheet

Part Number: 596-00860

Placards made with UV stable inks and materials tested to last up to 25 years, even in direct sun exposure.

Aggressive adhesive ensures strong bond, even on powder coated surfaces.

Meets or exceeds NEC & IFC standards for printed text, character height, color and outdoor UV stability.



Optional Paint Shields provide additional protection for pre-printed and variable data placards.

Metal Solar Placard, MAIN PV SYSTEM DISCONNECT, 5.5' x 1.75", AA, Red, 5/pkg

Article Number 596-00860

Type MPVSDM5

Color Red (RD)

Quantity Per pack

_			_	_				
ם	rn	a	Inct	Des	2 C Fi	ınt	10	n
	ıv	u	uCL	DC	36II	IDL	ıv	

Metal Solar Placards offer maximum durability and ease in code compliance. Perfect for solar applications, a special process seals metallic particles under a clear anodized layer, which results in markings that have been tested and rated to last up to 25 years in outdoor use, even in direct sunlight. Markers are designed to meet the latest National Electrical Code (NEC 2014), with pre-printed warning or caution messaging that conforms to Article 690, as well as ANSI guidelines. Pre-printed placards may be more acceptable to some local Authorities Having Jurisdiction (AHJs), who may have a preference for placard-style identification.

Short Description

Metal Solar Placard, MAIN PV SYSTEM DISCONNECT, 5.5' x 1.75", AA, Red, 5/pkg

Global Part Name

MPVSDM5-AA-RD

Technical Description

5.5" X 1.75" Black text on red background that reads as: "MAIN PV SYSTEM DISCONNECT." in 3/8" tall characters. 10 per pkg.

Local Order Number 2

Cross Reference = Paint Shield: 596-00795

Length L (Imperial)

5.5

Length L (Metric)

139.7

Width W (Imperial)

5.5

Width W (Metric)

139.7

Height H (Imperial)

1.75

Height H (Metric)

44.40

Material

Anodized Aluminum (AA)

Material Shortcut

AA

Adhesive

Ultra High Bond Permanent Acrylic Adhesive

Halogen Free

No

Adhesive Operating Temperature

from +50°F (from +10°C)

Operating Temperature

-40°F to +203°F (-40°C to +95°C)

Reach Compliant (Article 33)

Yes

ROHS Compliant

Yes

Certification/Specification

NEC2017

Warranty (US)

Yes

Package Quantity (Imperial)

5

Package Quantity (Metric)

5

Customs Number

7616995195

Labels per Column

1

Labels per Row

1

© 2021 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions