	<b>T</b>	G	П	m	τ	J	0	œ	A		_
4	R 22.6 Max	N Thread		S			<image/> <image/>	HOWN AS EXAMPLE			4
	Keying Shown as example										
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Ser	ies III	F	Connector dimensionDimNominalA34.9±0.3							
	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy			A         34.9±0.3           B         19.07+0.1/-0.15           R         32.5Max           S         31.8±0.4           W         2.2+0.9/-0.1           VV THREAD         M15x1-6g			due to a use of the the Specifications issued	liable for any non-conformity Products which does not com I by either of the Parties or by commendation, technical not	nply with v a third party		
N	-Seals & Grommet : Silicon Elastom -Contact Plating : Gold over copp	ier per Alloy 0.8μm minimum				<b></b>			ction & Control List Not Listed	]	2
	-Durability       : 500 Mating cycles         -Delivered with Souriau contacts and Accessories						PN: 8D711F98BA				
	-Temperature Range       : -65°C to +200°         -Salt Spray       : 48 hours         -Mass       : 20.65 g ± 10%	°C				A 30-09-201 ISS DATE	.6 First Release Latest modification - by			MOD N°	
					-	Designed By:	Date:		CUSTOMER DRAWING		_
	BASIC SERIES: 8D	0 7 - 11	F   98   B   A		-	SCALE		uminium Receptacle	NPRDS / PROJECT		_
<u> </u>	SHELL TYPE : Jam nut Receptacle					NA		blerances: ±	859	portu of	1
	CONTACT TYPE       : Standard Crimp Contact       ORIENTATION         SHELL SIZE : 11       CONTACT TYPE : SOCKET(500 Matir					SOURIAU WWW.SOURIAU.COM This document is the prope SOURIAU it must not be reproduced communicated without perm				ced or	
	PLATING : F = Nickel			CONTACT LAYO		FORMAT		URIAU DRG N° D711F98BA-C		SHEET 1/2	
L	Н	G	F	E	7	D	C C	B	A		

ſ	Т	G	П	т		0	σ	A		
4	Contact Layout $ \begin{array}{c}  & & & \\  & & \\$				Panel cutout JAM NUT RECEPTACLE (TYPE 7)					
	Shell Arrangement Numb size no. cont 11 -98 6	ion         X-axis         Y-axis (mm)           +.000 (0.00)         +.130 (3.30)           +.130 (3.30)         +.000 (0.00)           +.065 (1.65)        113 (2.87)          065 (1.65)        113 (2.87)          130 (3.30)         +.000 (0.00)           +.000 (0.00)         +.000 (0.00)           er of         Size         Service         Contact           rating         location         Supersedes					<u> </u>			
c.s						Dim         Nominal           B         19.59+0/-0.           ØC         20.96+0.25/			3	
						the Specifications issued by	ducts which does not com	nply with / a third party		
N						PN: 80		ction & Control List Not Listed	2	
					A 30-09-2010 ISS DATE Designed By:	6 First Release Latest modification - by Date:		MOD N CUSTOMER DRAWING	°	
<u> </u>					SCALE NA			NPRDS / PROJECT <b>859</b>	1	
		SOURIAU       WWW.SOURIAU.COM       This document is the property of SOURIAU it must not be reproduced or communicated without permission         FORMAT       SOURIAU DRG N°       S								
l	Н	G	F	E	A3	C 8D2	711F98BA-C B	A 2/2		