ſ	Т	۵	П	п		0
4	22.6 M		M Incad	S		
			Keying Sl	hown as example		
N	-Shell Plating: Nick-Insulator: Ther-Contacts: Copp-Seals & Grommet: Silico-Contact Plating: Gold-Durability: 500-Delivered with Souriau contact	iless Steel el moplastic ber Alloy on Elastomer over copper Alloy 0.8μm m Mating cycles	inimum	Connector dimension Dim Nomina A 38.1±0. B 23.82+0.1/ R 32.5Ma S 34.9±0. W 2.2+0.9/- VV THREAD M18x1-0	3 -0.15 ix 4 0.1 5g	SOURIAU shall due to a use the Specification (profess 3-09-2016 First Release
	-Salt Spray : 500	hours			A 28	DATE Latest modificat
_	BASIC SERIES: SHELL TYPE : Jam nut Recepta		13 S 03 S	N	Designed F	
	CONTACT TYPE : Standard C SHELL SIZE : 13			LCONTACT TYPE : SOCI		RIAU WWW
	PLATING : S = Nickel				T LAYOUT : 13-03	
					A3	
	Н	G	F	E	D	С

	σ		Þ			
					4	
LAYOUT SHOWN AS EXA	MPLE				3	
all not be liable for any non-conformity or damage use of the Products which does not comply with ons issued by either of the Parties or by a third party						
Country FR PN: 8D713SC	Jurisd	liction & Contr Not Listed	ol List		2	
ation - by te:		CUSTOMER	DRAWING	MOD N°		
Stainless Steel Receptacle 8D series						
General linear Tolerances: ±		NPRDS / 85	9		1	
W.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission						
SOURIAU E 8D713S03		I		SHEET 1/2		
	В		А			

	T O	m IF		C B	A
4	Contact Layout 03 () () () () () () () () () () () () ()			Panel cutout JAM NUT RECEPTACLE (TYPE 7)	4
ω	13-03 Ctc X Y A 2.39 1.47 B 0 -2.79 C -2.39 1.47			Dim Nominal B 24.26+0/-0.25 ØC 25.65+0.25/-0	3
2				FR	comply with or by a third party
			A 28-09-201 ISS DATE Designed By:	PN: 8D713S03SN L6 First Release Latest modification - by Date:	MOD N°
_			TITLE SCALE NA	Stainless Steel Recep General linear Tolerances: ±	NPRDS / PROJECT 859
			FORMAT A3	SOURIAU DRG N 8D713S03SN-C	
	H G I	F İ E	D	C B	A