



General Information		
Series	C87	
Dielectric	Film/Foil Polypropylene	
Style	Can	
Description	Aluminum Case, Plastic Cover, Spun Seal	
Features	Spun Seal, Safety Class S2, UL_94 V0 Disk	
RoHS	Yes	
Lead	Fast On (1+1)	
Qualifications	UL, VDE, CQC, CSA (240VAC), UL_94 V0 Disk	
AEC-Q200	No	
Component Weight	79 g	

SpecificationsCapacitance10 uFCapacitance Tolerance5%Voltage AC470 VACTemperature Range-25/+85°CRated Temperature85°CMax dV/dt20 V/us

Click here for the 3D model.

Dimensions	
D	35mm +1mm
L	78mm +/-2mm

Packaging Specifications		
Mounting	Bolt - M8x10	
Packaging	Bulk, Bag	
Packaging Quantity	86	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.