


ERP610W392KEFG

Aliases (C837EF392K760X, ERP610VH4390KEFG)

Obsolete

ERP610 SFTY X1–760 Y1–500, Ceramic, 3900 pF, 10%, 760 VAC (X1), 500 VAC (Y1), Y5U, Lead Spacing = 12.5mm





The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

General Information	1
Series	ERP610 SFTY X1-760 Y1-500
Style	Radial Disc
Description	Ceramic Single Layer Safety Disc Capacitors
RoHS	Yes
Termination	Tin
Qualifications	UL, CSA, CAN, ENEC, VDE
AEC-Q200	No

Specifications				
Capacitance	3900 pF			
Capacitance Tolerance	10%			
Voltage AC	760 VAC (X1), 500 VAC (Y1)			
Temperature Range	-40/+125°C			
Temperature Coefficient	Y5U			
Dissipation Factor	2.5%			
Insulation Resistance	10 GOhms			
Safety Class	X1/Y1			

(lick	here	tor	the	- XI)	model.

Dimensions	
D	15mm MAX
Т	5mm MAX
S	12.5mm NOM
LL	30mm -3mm
F	0.6mm +/-0.05mm
Α	6mm +/-1.5mm
V	2.1mm +/-0.5mm

Packaging Specifications	
Packaging	Bulk, Bag