## **Data Sheet**

### Coaxial Panel Connector 13\_BMA-50-0-1/199\_N

#### Description

Straight panel receptacle plug, flange mount

Interface standards IEC 60169-33\_MIL-STD-348A/321



#### **Technical Data**

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	18 GHz	
Mechanical Data		
Number of matings	1000	
Weight	0.0034 kg	
Environmental Data		
Operating temperature	-65 °C to 125 °C	
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant	
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Stainless Steel	
Body	Stainless Steel	

#### **Related Documents**

Catalogue drawing DCA-00011447
Ordering Information

Single package

Insulator

Gasket

13\_BMA-50-0-1/199\_NE

PFA / PTFE

NR (Natural Rubber)

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

# **HUBER+SUHNER**