

Coaxial PCB Connector 1x8A_82_MXPM-S50-0-1

Description

Straight PCB jack

Interface Standards

HUBER+SUHNER MXPM STD (Patent US 8,360,807 / Patent pend.)



Technical Data

Electrical Data

| | |
|--------------------------|-------------|
| Impedance | 50 Ω |
| Interface frequency max. | 70 GHz |

Mechanical Data

| | |
|---------------------|-------------------|
| Board mounting type | pin-in-hole / SMT |
| Weight | 0.0098 kg |

Environmental Data

| | |
|--|---------------|
| Operating temperature | 0 °C to 85 °C |
| 2011/65/EU (RoHS - including 2015/863 and 2017/2102) | compliant |

Material Data

| Piece Parts | Material | Surface Plating |
|----------------|----------|------------------------|
| Centre contact | | |
| Outer contact | Brass | SUCOPRO / Gold Plating |
| Body | Brass | SUCOPRO / Gold Plating |

Related Documents

| | |
|-------------------|--------------|
| Outline drawing | DOU-00332878 |
| Catalogue drawing | DCA-00364534 |

Ordering Information

| | |
|-----------------------|-----------------------------|
| Single package | 1x8A_82_MXPM-S50-0-1/-11_NE |
| Tape and Reel package | 1x8A_82_MXPM-S50-0-1/-11_NM |

Remarks

Multicoax socket, 1x8 ganged, keyed