T   G	m m		C	Φ		
4						4
CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown as example		LAYOUT SHOWN	I AS EXAMPLE		3
-Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts	ØS25 MaxZ31 MaxVV THREADM15x1-6g		the Specifications issued by eith (professional recomme	cts which does not comply w	ith rd party & Control List	2
-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours 		A 18-10-2016 ISS DATE Designed By:	First Release Latest modification - by Date:	CUST	MOD N	
BASIC SERIES: 8D 5 - 11 Z 0 SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	1 S B L Delivered W/O Con ORIENTATIO CONTACT TYPE : SOCKET(500 Mat	N:B SOURIAU	General lin Tolerance ±	U.COM	ies PRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or pommunicated without permission	1
PLATING : Z = Black Zinc Nickel	F E	1-01 FORMAT A3 D		AU DRG N° 1Z01SBL-C B	SHEET 1/2	

r	<u>т</u>	G	г П	m	U	0
		Contact Layout				
4		01				
	(	1#12 11-01	٦			
ω	Ctc A	X Y 0 0				
	<b> </b> -					SOURIAU shall not be liable for any due to a use of the Products wh
N						the Specifications issued by either of (professional recommendat Countr FR
					A 18-10-20 ISS DATE Designed By:	PN: 8D511Z
_					TITLE SCALE NA	Alumin General linear Tolerances: ±
					FORMAT A3	U WWW.SOURIAU.C SOURIAU 8D511Z0
l	Н	G	F	E	D	C C

Φ					
			4		
			3		
any non-conformit which does not co or of the Parties or k dation, technical no intry Jurisd	mply with by a third party		2		
	CUSTOMER DRAWING	MOD N°			
ninium Plug 8					
ir	NPRDS / PROJECT <b>859</b>				
.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission					
U DRG N° Z01SBL-C		SHEET 2/2			
B	A				