

RSBMC2330AA00K

Aliases (SBMC2330AA00K)

RSB, Film, Metallized Polyester Stacked, Automotive Grade, 0.033 uF, 10%, 400 VDC, 85°C, Lead Spacing = 5mm



Click [here](#) for the 3D model.

| Dimensions | |
|------------|-----------------|
| L | 7.2mm +0.3mm |
| H | 10mm +0.1mm |
| T | 5mm +0.2mm |
| S | 5mm +/-0.4mm |
| LL | 4mm +1.5mm |
| F | 0.5mm +/-0.05mm |

| Packaging Specifications | |
|--------------------------|------|
| Packaging | Bulk |
| Packaging Quantity | 1000 |

| General Information | |
|---------------------|--------------------------------------------------|
| Series | RSB |
| Dielectric | Metallized Polyester Stacked |
| Style | Radial |
| Features | Automotive Grade, DC Multipurpose Applications |
| RoHS | Yes |
| Lead | Cut |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Component Weight | 0.72 g |
| Miscellaneous | Above 85C DC And AC Voltage Derating Is 1.25%/C. |

| Specifications | |
|-----------------------|------------------------------------|
| Capacitance | 0.033 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 200 VAC |
| Voltage DC | 400 VDC |
| Temperature Range | -55/+125°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 0.8% 1kHz, 1.2% 10kHz, 2.5% 100kHz |
| Insulation Resistance | 30 GOhms |
| Max dV/dt | 600 V/us |
| Inductance | 7 nH |