

fuse GLDIII 500V, super quick acting



See below:
[Approvals and Compliances](#)

Description

- Characteristic gR
- According to IEC 269
- According VDE 0636
- Protection of semiconductors
- Time-current characteristic on request
- Cut-off current characteristic on request

Technical Data

Rated Current In	35- 63A
Rated Voltage	500VAC
Breaking Capacity	50kA
Rated Power Operating Frequency fe	50Hz

Basic Design

Insulator	Ceramic
Metal components	Brass

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

All Variants

Rated current [A]	Style [Compact]	Power Loss [W]	Order Number	E-No.
35	-	-	0034.1112	800323509
50	-	-	0034.1114	800325009
63	-	-	0034.1115	800326009

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

Packaging Unit 5 Pcs