

## Specification Sheet

Part Number: 170-03142



Braided Sleeving, Split Wrap, Flame Retardant, .5" Dia, PET, Black, 150 ft/bulk reel

**Article Number**

170-03142

**Type**

BSSWFR120B

**Color**

Black (BK)

**Features & Benefits**

- Split wrap design installs quickly, saving assembly time and future accessibility without disassembly.
- Unique construction retains shape and rigidity throughout operating temperature range.
- Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.
- Self wrapping design eliminates the need for fasteners.
- Provides a greater flexibility than spiralwrap or convoluted tubing.

**Quantity Per**

reel

**Product Description**

Used when flame retardancy is a primary requirement, this protection option incorporates a lateral split which allows the tube to open up to accommodate a variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners. Split wrap flame retardant braided sleeving is self-extinguishing and complies with UL VW-1 standards where cables exit a wall and need to be managed for an uncluttered, clean appearance.

**Short Description**

Braided Sleeving, Split Wrap, Flame Retardant, .5" Dia, PET, Black, 150 ft/bulk reel

**Global Part Name**

BSSWFR120B-PET-BK

**Length L (Imperial)**

150.0

**Length L (Metric)**

45.7

**Bundle Diameter Min (Imperial)**

0.5

**Bundle Diameter Min (Metric)**

12.7

**Bundle Diameter Max (Imperial)**

0.50

**Bundle Diameter Max (Metric)**

12.7

**Diameter D (imperial)**

0.50

**Diameter D (metric)**

12.7

**Nominal Diameter (Imperial)**

1/2

**Nominal Diameter (Metric)**

12.7

**Wall Thickness WT (Imperial)**

0.025

**Wall Thickness WT (Metric)** 0.64

**Material** Polyester (PET)

**Material Shortcut** PET

**Flammability** UL VW-1 FAR 25

**Halogen free** Yes

**Operating Temperature (Metric)** -94°F to +257°F (-70°C to +125°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 150

**Package Quantity (Metric)** 45.72

**Customs Number** 5808100000

**Weight (Metric)** 0.95

**Weight (Imperial)** 2.1

---

© 2019 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)