## ATGBICS AFBR-79E3PZ-AB1 Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)

Brand: ATGBICS Product code: AFBR-79E3PZ-AB1-C



**Product name :** AFBR-79E3PZ-AB1 Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)

AFBR-79E3PZ-AB1 Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM)

ATGBICS AFBR-79E3PZ-AB1 Avago Broadcom Compatible Transceiver QSFP+ 40GBase-CSR4 (850nm, MMF, 400m, MTP/MPO, DOM):



ATGBICS AFBR-79E3PZ-AB1 40GBase-CSR4 supports a distance of up to 400m over multi mode fibre (MMF) using a wavelength of 850nm via an MPO connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product meets the specification of AFBR-79E3PZ-AB1= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.

Performance		Features	
SFP transceiver type * Fiber optic  Maximum data transfer rate * 40000 Mbit/s  Interface type * QSFP+  Single-mode fiber (SMF) supported  Multi-mode fiber (MMF) supported  Fiber optic connector MPO  SFP transceiver standard CSR4  Maximum transfer distance 400 m  Wavelength 850 nm  Ethernet LAN	40000 Mbit/s QSFP+  MPO	Brand compatibility Certification	Avago Technologies CE, FCC, RoHS
		Power	
		Input voltage Maximum voltage	3.3 V 3.5 V
		Operational conditions	
	Maximum operating temperature 70 °C  Operating temperature (T-T) 0 - 70 °C  Storage temperature (T-T) -40 - 85 °C	0 - 70 °C	
Ethernet interface type	40 Gigabit Ethernet	Operating relative humidity (H-H)	0 - 95%
Digital Diagnostics Monitoring (DDM)	<b>√</b>	Storage relative humidity (H-H)	0 - 95%
Wavelength-division multiplexing (WDM)	×	Weight & dimensions	
		Width	13.5 mm
Features		Depth	72.4 mm
Product colour Silver Housing material Metal Plug and Play	Silver Metal	Height Weight	18.4 mm 42 g
		Packaging data	
Hot-Plug support	✓	Number of products included	1 pc(s)
Hot-swap	✓	Package type	Box
Easy to install Country of origin	✓ United Kingdom	Technical details	
		Sustainability compliance Sustainability certificates Doesn't contain	✓ RoHS Lead



5056468752598

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.