


ARR07B393KWS

ARR Indust X7R HT200C, Ceramic, 0.039 uF, 10%, 50 VDC, X7R, Commercial, High Temperature, Lead Spacing = 5.08mm



Click	here	for	the	3D	model.
-------	------	-----	-----	----	--------

Dimensions	
L	7.62mm MAX
W	7.62mm MAX
Т	3.81mm MAX
S	5.08mm +/-0.38mm
LL	3.175mm MIN
F	0.508mm +/-0.051mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	1

General Information	
Series	ARR Indust X7R HT200C
Style	Radial
Description	Commercial, High Temperature
Features	Commercial
RoHS	No
Prop 65	WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.
SCIP Number	6906e33d-ee54-4964-bee2-22e2ed2d0d24
Termination	Lead (SnPb)
Failure Rate	N/A
Testing and Reliability	Standard
AEC-Q200	No

Specifications					
Capacitance	0.039 uF				
Capacitance Tolerance	10%				
Voltage DC	50 VDC				
Dielectric Withstanding Voltage	125 VDC				
Temperature Range	-55/+200°C				
Temperature Coefficient	X7R				
Dissipation Factor	2.5%1kHz1.0Vrms				
Insulation Resistance	25.641 GOhms				

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.