


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00026	Connector, dc plug, 5.5x2.5xL23 mm, molding style, spring contacts	1	
2	30-00440	Wire, 2C TS, 16 AWG, UL2468, 300V, 80C, 4.8 mm, VW-1, PVC, 87A	1	
3	24-00003	Overmold, PVC	1	black



Notes:
Functionally equivalent components may be substituted

Wiring Diagram	
50-00026	wire color
center	black with stripe
sleeve	black

Revision:	Date:	Description:	Prepared:	Notes:	<h1>TENSILITY</h1> tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	11/22/2016	Initial release	AW <small>Digitally signed by AW Date: 2018.06.12 11:32:10 -07'00'</small>		
			Verified:	Function test: no open, no short circuit, no intermittent	Size:
			AG <small>Digitally signed by AG Date: 2018.06.12 16:32:55 -07'00'</small>	Description:	Part number:
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Cable, 3050 mm, 5.5x2.5x12 mm 50-00026 dc plug to stripped tinned, 16 AWG, 30-00440 wire	A 10-02388
					Scale: 1:1
					Sheet 1 of 1

5

4

3

2

1