




## Aliases (10HS36B474K)

HS RAD-LDD Space X7R HV, Ceramic, 0.47 uF, 10%, 1000 VDC, X7R, Lead Spacing = 34.92mm



Click here for the 3D model.

Dimensions	
L	36.83mm
Н	18.29mm MAX
т	6.89mm MAX
S	34.925mm +/-0.762mm
LL	31.75mm MIN
F	0.635mm NOM

Bulk, Bag

Packaging Specifications	
Pac	:kaging

5 5	
Packaging Quantity	1

General Information		
Series	HS RAD-LDD Space X7R HV	
Style	Radial	
RoHS	No	
Prop 65	A WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	2340ecb8-2b2f-4a8e-990d-e9ce728f4668	
Termination	Lead (SnPb)	
Failure Rate	N/A	
AEC-Q200	No	

Specifications			
Capacitance	0.47 uF		
Capacitance Tolerance	10%		
Voltage DC	1000 VDC		
Dielectric Withstanding Voltage	1500 VDC		
Temperature Range	-55/+125°C		
Temperature Coefficient	X7R		
Dissipation Factor	2.5%		
Insulation Resistance	2.1 GOhms		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.