THIS IS A C.A.D. GENERATED DRAWING DO NOT MAKE MANUAL REVISIONS TO MASTER.

MATERIALS:

8.





WIRE-HOUSING SEAL: SILICON RUBBER

ISSUE NUMBER

1

ORIGINAL





SPECIFICATIONS: PITCH: 2.0MM 2. 3. **RATED VOLTAGE: 250V**


RATED CURRENT: 2A MAX WITHSTAND VOLTAGE: AC1000V R.M.S. 5. CONTACT RESISTANCE: 10 mOHMS MAX


INSULATION RESISTANCE: 1000 MOHMS MIN/DC 500V

HOUSING: PBT, UL94V-0

TEMPERATURE RANGE: -40°C ~ +105°C WATERPROOF GRADE: TESTED AND

CERTIFIED TO IP67





ITEM NO.	DESCRIPTION	QTY.
1	566-002-000-811_Housing	1
2	566-002-000-811_Rubber	1

566 SERIES 2 SOCKET WATERPROOF CONNECTOR

EDAC INC

ACAD REFERENCE NO. 566 ASSEMBLY DATE: JUL.30/2014 DRAWN:R.STA.MONICA CHECKED: DATE: SCALE: NOT TO SCALE SHEET 1 OF 1 ISSUE

TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC., AND SHALL NOT BE REPRODUCED, OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWING NUMBER 566-002-000-811



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY