Mounting Option In-Line Card Guides **Contact Detail** 90 Degree Bend (Code 522 and 540 Contacts) .156 [3.96] Contact Spacing x .200 [5.08] Row Spacing 4.054 [102.97] 3.908 [99.26] 0.343 [8.71] 0.473 [1/2.01] .175 [4.45] Point of Contact (Measured from bottom of Card Slot) EDRG

See Accompanying Pages for:

- Contact Bend Details
- Mounting Options
- Features and Specifications

807 Series High Temp Card Edge Connector Part Number: 807-024-559-178

EDNG

EDAC INC TORONTO, ONTARIO CANADA

CANADA OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF AF WITHOUT WRITTEN PERMISSION.

| ACAD REFERENCE NO. 807 ENG MASTER | | | | |
|-----------------------------------|------------------|--|--|--|
| DRAWN: J.LEE | DATE: AUG. 11/09 | | | |
| CHECKED: | DATE: | | | |
| SCALE: NTS | SHEET 1 OF 4 | | | |
| DRAWING NUMBER | ISSUE | | | |
| 807 Assembly | 1 | | | |

SECTION A-A

Card Slot Accepts .054 [1.37] to .070 [1.78] Thick P.C. Board





ISSUE NUMBE

ORIGINAL



Features

- CSA Approved and UL Recognized
- .156 (3.96) Contact Spacing x .200 (5.08) Row Spacing
- Accepts .062 (1.57) Nominal Thickness P.C. Board
- Low Profile Insulator Body .473 (12.01), with Card Guides
- Contact Termination Options include P.C. Tail, Wire Hole, Wire Wrap, 90 Degree & Extender Board Bends
- Single or Dual Row Configurations
- Large Variety of Mounting Options
- Pre-assembled Card Guides Available
- Accepts Between Contact and In-Contact Polarizing Keys

Specifications

- Insulator Material: DAP
- Contact Material: Copper, Nickel, Tin Alloy CA-725
- Contact Plating: Gold on the Mating Area, Tin on the Contact Tails, Nickel Underplate
- Current Rating: 5 Amperes Continuous
- Contact Resistance: 10 Milliohms Maximum
- Dielectric Withstanding Voltage: 1800 V AC rms at Sea Level Between Adjacent Contacts
- Insulation Resistance: 5000 Megohms Minimum
- Operating Temperature: -65 to +165 °C
- Insertion Force: 16 oz (4.45 N) Maximum per Contact Pair when Tested with a .070 (1.78) Thick Gauge
- Withdrawal Force: 1 oz (0.28 N) Minimum per Contact Pair when Tested with a .054 (1.37) Thick Gauge

| 807 Series High Temp Card Edge Connector Features and Specifications | | ACAD REFERENCE NO. 807 ENG MASTER | | | |
|---|------------------------------------|-----------------------------------|-------------|----------|----------|
| | | DRAWN: | J.LEE | DATE: AU | G. 11/09 |
| | | CHECKED: | | DATE: | |
| EDAC INC | ARE THE RECREETLY OF EDAG INC. AND | SCALE: | NTS | SHEET . | 4 OF 4 |
| TORONTO, ONTARIO | | DRAWING | NUMBER | | ISSUE |
| CANADA OR USED AS THE BASIS FOR TI MANUFACTURE OR SALE OF APP WITHOUT WRITTEN PERMISSION. | | 8 | 07 Assembly | | 1 |