


## C052C472J1G5TA

Aliases (C052C472J1G5TA)

LDD Comm COG, Ceramic, 4700 pF, 5%, 100 VDC, COG, Lead Spacing = 5.08 mm



Click here for the 3D model.

Dimensions	
L	4.83mm +/-0.25mm
Н	4.83mm +/-0.25mm
Т	2.29mm +/-0.25mm
S	5.08mm +/-0.38mm
LL	31.75mm MIN
F	0.635mm +0.102/-0.051mm
G	1.143mm MAX

Packaging Specifications	,
Packaging	Bulk, Bag
Packaging Quantity	100

General Information		
Series	LDD Comm COG	
Style	Radial	
Features	Commercial	
RoHS	With Exemptions	
REACH	SVHC (Pb - CAS 7439-92-1)	
SCIP Number	ff8834ac-5013-4064-ad05-4cd1f8f13378	
Termination	Tin	
Failure Rate	N/A	
AEC-Q200	No	

Specifications	
Capacitance	4700 pF
Capacitance Tolerance	5%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Dissipation Factor	0.1% 1 kHz 25C
Insulation Resistance	213 MOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.