




## VMT30-15-M8-55-S/5PK

Ruland VMT30-15-M8-55-S/5PK, 5 Pack Of Rubber Bumpers, 30mm OD, M8 Tapped Hole, 8mm Tapped Hole Depth, 15mm Height, 55 Shore A Natural Rubber Jacket, Stainless Steel

**5** pack



### Description

Ruland VMT30-15-M8-55-S/5PK is a 5 pack of rubber bumpers, each with a tapped hole. An individual rubber bumper has 30mm outside diameter, M8 tapped hole, 8mm tapped hole depth, and 15mm height. Rubber bumpers are used to dampen shock loads and reduce noise and wear on industrial equipment, machine doors, and floors or other surfaces which allows for a safer and more pleasant working environment. They are often referred to as a sandwich mount or rubber buffer because they function as a shock or vibration isolator sandwiched between two machine components or surfaces. These rubber bumpers have a cylindrical shape allowing for even distribution of shock loads. A rubber bumper can be mounted to the system by threading it onto an existing stud on the components. The rubber jacket is made from natural rubber which has good elasticity and is well suited for most industrial equipment. Rubber bumpers in this pack have 55 Shore A hardness for a balance of rigidity and shock absorption. Bodies are made from stainless steel allowing for increased corrosion resistance. These rubber bumpers are manufactured by Otto Ganter, inventoried by Ruland, and RoHS3 compliant.

### Product Specifications

<b>Outer Diameter (OD)</b>	1.18 in (30 mm)	<b>Height (H1)</b>	0.59 in (15 mm)
<b>Thread (TH)</b>	M8 x 1.25	<b>Plate Thickness (PT)</b>	0.08 in (2 mm)
<b>Tapped Hole Depth (LT)</b>	0.31 in (7.9 mm)	<b>Spring Rate</b>	1570.29 lb/in (275 N/mm)
<b>Shore Hardness</b>	55A (+/- 5)	<b>Max Deflection</b>	0.15 in (3.8 mm)
<b>Max Axial Load</b>	229.31 lb (1020 N)	<b>Multipack Quantity</b>	5
<b>Geometry</b>	Cylindrical	<b>Rubber Material</b>	Natural Rubber
<b>Metal Material</b>	Stainless Steel	<b>Metallic Body Finish</b>	Bright
<b>Country of Origin</b>	Hungary	<b>Weight (lbs)</b>	0.247900
<b>UPC</b>	634529313138	<b>Tariff Code</b>	4016.99.6000
<b>UNSPC</b>	31162804		
<b>Note 1</b>	Performance ratings are for guidance only. The user must determine suitability for a particular application.		
<b>Prop 65</b>	⚠️ <b>WARNING</b> This product can expose you to chemicals including Soots and Nickel (metallic)		