

# **Material Safety Data Sheet**

Copyright, 2004, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This material safety data sheet (MSDS) is provided as a courtesy in response to a customer request. This product is not regulated under, and a MSDS is not required for this product by the OSHA Hazard Communication Standard (29 CFR 1910.1200) because, when used as recommended or under ordinary conditions, it should not present a health and safety hazard. However, use or processing of the product not in accordance with the product's recommendations or not under ordinary conditions may affect the performance of the product and may present potential health and safety hazards.

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M<sup>™</sup> DOUBLE COATED TAPE 9492MP, 9492MPF, 9495MP, 9495MPF and 9495FL

**MANUFACTURER: 3M** 

**DIVISION:** Industrial Adhesives and Tapes

**ADDRESS:** 3M Center

St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 03/31/2004 **Supercedes Date:** Initial Issue

**Document Group:** 19-1881-2

**Product Use:** 

Specific Use: ATTACHMENT

## **SECTION 2: INGREDIENTS**

IngredientC.A.S. No.% by WtACRYLATE COPOLYMER ADHESIVENONE80 - 95POLYESTER CARRIERNONE5 - 20

## **SECTION 3: HAZARDS IDENTIFICATION**

#### 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Roll of Tape

Odor, Color, Grade: Clear tape. Acrylate odor.

General Physical Form: Solid

Immediate health, physical, and environmental hazards: The environmental properties of this product present a low

environmental hazard. This product, when used under reasonable conditions and in accordance with the 3M directions for use, should

# 3M MATERIAL SAFETY DATA SHEET 3m<sup>™</sup> DOUBLE COATED TAPE 9492MP, 9492MPF, 9495MP, 9495MPF and 9495FL 03/31/2004

not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

#### 3.2 POTENTIAL HEALTH EFFECTS

#### **Eye Contact:**

No health effects are expected.

#### **Skin Contact:**

No health effects are expected.

#### **Inhalation:**

No health effects are expected. This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### **Ingestion:**

No health effects are expected.

#### 3.3 POTENTIAL ENVIRONMENTAL EFFECTS

This substance does not leach metals or other RCRA (Resource Conservation and Recovery Act) listed TCLP (Toxic Characteristic Leaching Procedure) hazardous substances at concentrations that would make the product a hazardous waste.

## **SECTION 4: FIRST AID MEASURES**

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** No need for first aid is anticipated.

**Skin Contact:** No need for first aid is anticipated.

**Inhalation:** No need for first aid is anticipated.

**If Swallowed:** No need for first aid is anticipated.

## **SECTION 5: FIRE FIGHTING MEASURES**

#### 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot Applicable

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** No unusual fire or explosion hazards are anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Accidental Release Measures: Not applicable.

## **SECTION 7: HANDLING AND STORAGE**

## 7.1 HANDLING

Avoid prolonged or repeated skin contact. This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

#### 7.2 STORAGE

Not applicable.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 ENGINEERING CONTROLS

Not applicable.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

## 8.2.1 Eye/Face Protection

Avoid eye contact.

#### 8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required.

### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

#### 8.2.4 Prevention of Swallowing

Not applicable.

## 8.3 EXPOSURE GUIDELINES

None Established

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 3M MATERIAL SAFETY DATA SHEET $3m^{TM}$ DOUBLE COATED TAPE 9492MP, 9492MPF, 9495MP, 9495MPF and 9495FL 03/31/2004

Specific Physical Form: Roll of Tape

Odor, Color, Grade: Clear tape. Acrylate odor.

General Physical Form: Solid

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot ApplicableBoiling pointNot ApplicableDensityNot ApplicableVapor DensityNot Applicable

Vapor Pressure Not Applicable

Specific GravityNo Data AvailablepHNot ApplicableMelting pointNot Applicable

Solubility in Water Nil

Evaporation rateNot ApplicablePercent volatileNot ApplicableViscosityNot Applicable

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid: None known

**Hazardous Polymerization:** Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

SubstanceConditionHydrocarbonsDuring Combustion

Carbon monoxide During Combustion
Carbon dioxide During Combustion
During Combustion

**Hazardous Decomposition:** Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products may occur as a result of oxidation, heating, or reaction with another material.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

## **ECOTOXICOLOGICAL INFORMATION**

Not applicable.

#### CHEMICAL FATE INFORMATION

Not applicable.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Reclaim if feasible. If product can't be reclaimed, dispose of waste product in a sanitary landfill. Alternatively, incinerate the waste product in an industrial, commercial, or municipal incinerator. Dispose of waste product in a sanitary landfill. As a disposal alternative, incinerate in an industrial or commercial facility.

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14:TRANSPORT INFORMATION

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

# **SECTION 15: REGULATORY INFORMATION**

## US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - No Delayed Hazard - No

#### STATE REGULATIONS

Contact 3M for more information.

#### **CHEMICAL INVENTORIES**

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

#### **NFPA Hazard Classification**

Health: 0 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the

# 3M MATERIAL SAFETY DATA SHEET 3m<sup>™</sup> DOUBLE COATED TAPE 9492MP, 9492MPF, 9495MP, 9495MPF and 9495FL 03/31/2004

inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com