

PRODUCT DATASHEET FCP15708_FLORENTINA-4X1-MRK-S

FLORENTINA-4X1-MRK-S

 ${\sim}25^\circ$ spot beam. Compatible with ultra high power LEDs.

TECHNICAL SPECIFICATIONS:

Dimensions	169.7 x 49.7 mm
Height	29.7 mm
Fastening	pin, screw
ROHS compliant	yes 🛈



MATERIAL SPECIFICATIONS:


Component	Туре	Material	Colour	Finish
ROSE-MRK-S	Single lens	PC	clear	
FLORENTINA-4X1-HLD	Holder	PC	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCP15708_FLORENTINA-4X1-MRK-S	Single lens	72	72	8	3.3
» Box size: 476 x 273 x 292 mm					



PRODUCT DATASHEET FCP15708_FLORENTINA-4X1-MRK-S



See also our general installation guide: <u>www.ledil.com/installation_guide</u>



PHOTOMETRIC DATA (MEASURED):

OSRAM Opto Semiconductors LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic Light colour Required compone C15198_FLOR	OSCONIQ P 7070 29.0° / 52.0° 71 % 2 cd/lm 1 White ents: ENTINA-4X1-SHD-OPEN	
OSRAM Opto Semiconductors LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic Light colour Required compone C15690_FLOR	OSCONIQ P 7070 29.0° / 53.0° 77 % 2 cd/lm 1 White ents: ENTINA-4X1-SHD-WHT	
OSRAM Opto Semiconductors LED FWHM / FWTM Efficiency Peak intensity LEDs/each optic Light colour Required compone C15028_FLOR	OSCONIQ P 7070 28.0° / 52.0° 0 % 2.1 cd/lm 1 White ents: ENTINA-4X1-SHD	



PHOTOMETRIC DATA (SIMULATED):

OSRAM Opto Semiconductors		90°
LED	Duris S8	75
FWHM / FWTM	30.0° / 56.0°	
Efficiency	78 %	00- 00- 00- 00- 00- 00- 00- 00- 00- 00-
Peak intensity	2.4 cd/lm	
LEDs/each optic	1	
Light colour	White	gr at
Required component	is:	
C15028_FLOREN	ITINA-4X1-SHD	31° 20° 20° 30°



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc. 228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd. # 405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy