


R523R410050P0K

Aliases (523R410050P0K)

R52 310 VAC MINI, Film, Metallized Polypropylene, Automotive Safety, 1 uF, 10%, 310 VAC (X2), 630 VDC, 110 °C, Lead Spacing = 27.5 mm



Click here for the 3D model.

Dimensions	
L	32mm +0.3/-0.7mm
Н	17mm +0.1/-0.7mm
Т	9mm +0.2/-0.7mm
S	27.5mm +/-0.4mm
LL	25mm +2/-1mm
F	0.8mm +/-0.05mm

Packaging Specifications	
Packaging	Tray
Packaging Quantity	408

General Information		
Series	R52 310 VAC MINI	
Dielectric	Metallized Polypropylene	
Style	Radial	
Features	EMI Safety	
RoHS	Yes	
Lead	Wire Leads	
Safety Class	X2	
Qualifications	ENEC, UL, cUL, CQC, AEC-Q200	
AEC-Q200	Yes	
THB Performance	Yes	
Component Weight	6.38 g	

Specifications				
Capacitance	1uF			
Capacitance Tolerance	10%			
Voltage AC	310 VAC (X2)			
Voltage DC	630 VDC			
Temperature Range	-40/+110°C			
Rated Temperature	110°C			
Dissipation Factor	0.2% 1kHz			
Insulation Resistance	30 GOhms			
Max dV/dt	150 V/us			

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.