

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

USB-C Dock - 4K HDMI, USB 3.2 Gen 1, USB-A/C Hub, GbE, Memory Card, 60W PD Charging

MODEL NUMBER: U442-DOCK11-S









USB-C dock with PD Charging adds 4K HDMI, USB-A, USB-C and Ethernet ports to your laptop or tablet's USB-C or Thunderbolt 3 port.

Features

USB-C Docking Station Turns Your Device's USB-C or Thunderbolt 3 Port into a WorkstationThis multiport USB-C dock with PD Charging expands the potential of your Windows laptop, Chromebook, tablet or other device with a USB-C or Thunderbolt 3 port. It's ideal for connecting to a wired Gigabit Ethernet network, transmitting digital audio and video to a large display, adding a thumb drive or other USB peripheral, powering and charging a PD Charging-compliant mobile device and more—all at the same time.

Supports USB-C DisplayPort Alternate Mode for Transmitting Audio/Video SignalsBy connecting the built-in USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to a compatible monitor, television or projector without installing special software drivers.

Transmits Crystal-Clear 4K Video and Digital AudioThe HDMI port supports Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 30 Hz. A DVI display may also be connected using an HDMI to DVI adapter (sold separately). HDCP 2.2 compliance allows you to stream 4K Amazon and Netflix content with no complications.

Accesses a Wired Gigabit Ethernet NetworkThe RJ45 port offers access to a Gigabit Ethernet network when no Wi-Fi is available or when a wired connection offers faster speeds. Connect using a UTP cable (sold separately), and enjoy true 10/100/1000 Mbps Ethernet speeds for fast data transfers.

USB Ports Connect Keyboards, Thumb Drives and Other USB PeripheralsTwo USB 3.2 Gen 1 ports accept USB peripherals, such as flash drives, mice, keyboards and printers. They support fast data transfer rates up to 5 Gbps and are backward compatible with USB 2.0 and USB 1.1 devices. Note: Host must support USB OTG (On-the-Go).

PD 2.0 Charging Port Charges Connected Device via AC Wall ChargerThe USB-C Power Delivery port supports power output up to 20V 3A (60W), which is sufficient for charging and powering the connected source device, such as an Android smartphone or Chromebook. Just connect the device's AC wall charger to the USB-C PD port. This port can also be used for transferring data up to 5 Gbps. Note: USB-C PD port does not support Quick Charge (QC).

Allows External Memory AccessMemory card slots support Micro SD and SD/MMC cards for transferring data to and from your connected computer, laptop or tablet. Both memory card slots can be used at the same time.

Built-In USB-C Cable Connects in Either DirectionConnect the reversible USB-C plug to your source device's USB-C or Thunderbolt 3 port. The fumble-free USB-C plug connects in either direction to ensure fast, easy connection every time.

Ready to Use Right Out of the PackageThe plug-and-play USB-C dock is specifically designed for use with Windows laptops and other notebooks, smartphones, tablets and devices equipped with a USB-C or Thunderbolt 3 port. It requires no extra software to be downloaded or installed. The compact unit fits

Highlights

- Transmits audio/video signals from sources supporting USB DisplayPort Alt Mode
- Supports Ultra HD 4K resolutions up to 3840 x 2160 @ 30 Hz for crystal-clear video
- Joins a wired 10/100/1000
 Gigabit Ethernet network when no Wi-Fi is available
- Supports 20V 3A (60W) power output for fast-charging compatible mobile devices
- USB-C, USB-A and memory card ports allow connection of flash drives and other peripherals

Applications

- Play video from your laptop or PC on an HDMI display, such as an HDTV or projector
- Access a wired Ethernet network in a location with no or spotty Wi-Fi
- Charge your notebook or laptop by connecting its wall charger to the USB-C PD Charging port
- Transfer data to and from a USB flash drive or memory card
- Connect a microphone/headset to record a podcast or listen to music

System Requirements

 Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode



easily into a pocket, briefcase or laptop bag for connecting on the go. If additional power is required, the 5V DC power jack is compatible with power supplies (not included) equipped with a $3.5 \times 1.35 \times 9.5$ millimeter output plug, a positive tip and a negative sleeve.

- Display device with HDMI or DVI* input
- Not for use with Thunderbolt

monitors *Requires adapter (sold separately)

Package Includes

• U442-DOCK11-S USB-C Dock,

Silver

• Owner's manual

Specifications

OVERVIEW		
UPC Code	037332213372	
Product Type	Docking Station	
Technology	HDMI; USB; USB 3.0 (SuperSpeed); USB 3.1 (Gen 1); PD Charging	
Host Connector	USB C (MALE)	
VIDEO		
Number of Monitors Supported	1	
Video Ports	HDMI (FEMALE)	
Video Ports Detail	HDMI 2.0; HDCP 2.2	
Resolutions Supported	HDMI: 4K 30Hz (3840 x 2160)	
Max Supported Video Resolution	HDMI: 3840 X 2160 (4K X 2K) @ 30HZ	
Extended Mode	No	
Mirror Mode	No	
Max Supported Color Depth	24-bit True Color	
Chroma Sub Sampling	4:4:4	
DATA		
Data Ports	(1) USB C (FEMALE); (2) USB A (FEMALE)	
Data Ports Detail	(1) USB-C - USB 3.2 Gen 1 (5 Gbps); (2) USB-A - USB 3.2 Gen 1 (5 Gbps)	
NETWORK		
Network Ports	RJ45 (FEMALE)	



Card Slots SD (FEMALE); MICRO SD (FEMALE) Card Slots Detail Both card readers can be used at the same time NPUT State Card Slots State Card Slots Valage Compatibility (VAC) 100. 110. 120; 127, 200; 208; 220; 230; 240 Slot Card Slots Built-In Cable Length (m) 0.49 Slot Card Slots Built-In Cable Length (m) 0.55 Slot Card Slot Carg (m) Built-In Cable Length (m) 15 Slot Card Slot Carg (m) Built-In Cable Length (m) 12 Slot Card Slot Carg (m) Built-In Cable Length (m) 12 Slot Card Slot Carg (m) Product Length (m) 1 Slot Card Slot Carg (m) Bits Orbard Length (m,) 1 Slot Card Slot Slot Slot (m) Product Length (m,) 1 Slot Card Slot Slot Slot Slot (m) Product Length (m,) 1 Slot Slot Slot Slot Slot Slot Slot Slot			
Carl Stets Detail Both card readers can be used at the same time INPUT Voltage Compatibility (VAC) 100: 110: 120: 127: 200: 208: 220: 230: 240 Built-In Cable Length (II.) 0.49	STORAGE		
INPUT Voltage Compatibility (VAC) 100; 110; 120; 127; 200; 208; 220; 230; 240 Built Compatibility (VAC) 0.49 Built Compatibility (VAC) 0.15 Built Compatibility (VAC) 0.15 Built Compatibility (VAC) 15 Built Compatibility (VAC) 12 Product Length (m.) 12 Product Length (m.) 0.3 Batter Charging (K/1, 5A Port) 0.3 Power No Statury Charging (SV/1, 5A Port) No Power Second Compatibility (PD) Charging Specification SV/2A External Power Supply DC Barrel OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sizeeve USB Power Delivery (PD) Charging Yes USB Power Delivery (PD) Charging Yes USB Power Delivery (PD) Charging 2.0 USB Power Delivery (PD) Charging 2.0			
Votage Compatibility (VAC) 100: 110: 120: 127: 200: 208: 220: 230: 240 Built-In Cable Length (ft.) 0.49 Built-In Cable Length (m) 0.15 Built-In Cable Length (m) 5.9 Built-In Cable Length (m) 15 Built-In Cable Length (m) 12 Product Length (m) 0.48 Product Length (m) 0.48 Product Length (m) 0.3 Battery Charging (5V1.5A Port) 0.3 Product Length (m) 0.3 Battery Charging (5V1.5A Port) No Product Length (m) 0.3 Battery Charging (5V1.5A Port) No Provers Supply Output Statemal Power Supply Output St/2A Statemal Power Supply Output St/2A Statemal Power Supply Charging V2A USB Power Delivery (PD) Charging Y2A USB Power Delivery (PD) Charging 2.0 USB Power Delivery (PD) Charging 2.0 USB Power Delivery (PD) Charging (2) 0.54: 34 LED Indicators VHe (Power), Green (Link), Yellow (Activity) Charging Ports /	Card Slots Detail	Both card readers can be used at the same time	
Built-In Cable Length (tt.) 0.49 Built-In Cable Length (m) 0.15 Built-In Cable Length (m) 5.9 Built-In Cable Length (m) 15 Built-In Cable Length (m) 15 Built-In Cable Length (m) 12 Product Length (n.) 12 Product Length (m.) 0.3 Battery Charging (5V/1.5A Port) 0.3 Product Length (m.) 0.3 Battery Charging (5V/1.5A Port) No Powere External Power Supply Output Sv/2A Spees (V./A) Sv/2A External Power Supply OLtput Sv/2A Spees (V.A) Sv/2A USB Power Delivery (PD) Charging Yes USB Power Delivery (PD) Charging 2.0 USB Power Delivery (PD) Charging Sves USB Power Delivery (PD) Charging Wite (Power), Green (Link), Yellow (Activity) Charging Ports / Amps (2) 0.9A; 3A Charging Ports / Amps (2) 0.9A; 3A Charging Ports / Amps (2) 0.9A; 3A Charging Ports UBA: CioW (20 VA) Power Delivery (PD 2	INPUT		
Built-In Cable Length (m) 0.15 Built-In Cable Length (m) 5.9 Built-In Cable Length (cm) 15 Built-In Cable Length (cm) 12 Product Length (m). 30.48 Product Length (m). 1 Product Length (m). 0.3 Battery Charging (5V/1.5A Port) No Powere 5V/2A External Power Supply Output 5V/2A Spess (V / A) Sv/2A Spess (V / A) Sv/2A USB Power Delivery (PD) Charging Sv/2A USB Power Delivery (PD) Charging Sv/2A USB Power Delivery (PD) Charging Svest Support Delivery (PD) Charging Svest USB Power Delivery (PD) Charging Svest Support Polivery (PD) Charging Svest USB Power Delivery (PD) Charging Svest Support Polivery (PD) Charging Svest Support Polivery (PD) Charging Svest USB Power Delivery (PD) Charging Svest Support Polivery (PD) Charging Svest Support Delivery (PD) Charging Svest	Voltage Compatibility (VAC)	100; 110; 120; 127; 200; 208; 220; 230; 240	
Built-In Cable Length (in) 5.9 Built-In Cable Length (cm) 15 Bus Powered Yes Product Length (in) 12 Product Length (cm.) 30.48 Product Length (rm.) 1 Product Length (rm.) 0.3 Battery No Powere Sv2A External Power Supply Output Specs (V / A) Sv/2A External Power Supply Output Specs (V / A) Sv/2A USB Power Delivery (PD) Charging Support Delivery (PD) Charging Yes USB Power Delivery (PD) Charging Support Delivery (PD) Charging 2.0 USER INTERFACE, ALERTS & CONSTRUCT Verial Constructor Specification USB Power Delivery (PD) Charging Support Delivery (PD) Charging Verial Constructor Specification USB Power Delivery (PD) Charging Specification Verial Constructor Specification USB Power Delivery (PD) Charging 2.0 Charging	Built-In Cable Length (ft.)	0.49	
BuiltIn Cable Length (cm) 15 Bus Powered Yes Product Length (m) 12 Product Length (cm.) 30.48 Product Length (tm.) 1 Product Length (tm.) 0.3 Battery Charging (5V/1.5A Port) No Product Length Power Supply Output 5V/2A External Power Supply Output 5V/2A External Power Supply Output SV/2A USB Power Delivery (PD) Charging 2.0 USB Power Delivery (PD) Charging <td>Built-In Cable Length (m)</td> <td>0.15</td>	Built-In Cable Length (m)	0.15	
Bus Powered Yes Product Length (m.) 12 Product Length (m.) 30.48 Product Length (m.) 0.3 Battery Charging (SV/1.5A Port) 0.3 Battery Charging (SV/1.5A Port) No POWER External Power Supply Output External Power Supply Output SV/2A External Power Supply DC Barrel OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging Yes USB Power Delivery (PD) Charging 2.0 USB Power Delivery (PD) Charging Yes LED Indicators White (Power), Green (Link), Yellow (Activity) Charging Ports / Amps (2) 0.9A: 3A Charging Watts 60	Built-In Cable Length (in.)	5.9	
Product Length (in.) 12 Product Length (in.) 30.48 Product Length (ti.) 1 Product Length (ti.) 0.3 Batter Charging (5V/1.5A Port) No Power September 2000 Power Supply Output 50/2A Sternal Power Delivery (PD) Charging 1 Sternater Power Delivery (PD) Charging 1 Sternater Power Delivery (PD) Charging 1 Sternater Power Delivery (PD) Charging 1 Charging Ports / Amps (2) 0.9A; 3A Charging Ports / Amps (2) 0.9A; 3A Charging Ports / Amps (2) 0.9A; 3A<	Built-In Cable Length (cm)	15	
Product Length (cm.) 30.48 Product Length (ft.) 1 Product Length (m.) 0.3 BATTERY Battery Charging (5V/1.5A Port) No POWER External Power Supply Output Specs (V / A) 5V/2A External Power Supply DC Barrel Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging Support Yes USB Power Delivery (PD) Charging Support 2.0 USER INTERFACE, ALERTS & CONCERTING Charging Ports / Amps (2) 0.9A: 3A Charging Ports / Amps (2) 0.9A: 3A Charging Ports / Amps (2) 0.9A: 3A Charging Ports USB -C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	Bus Powered	Yes	
Product Length (ft.) 1 Product Length (ft.) 0.3 BATTERY Battery Charging (5V/1.5A Port) No POWER External Power Supply Output Sorges (V / A) 5V/2A External Power Supply DC Barrel Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging Specification Yes USB Power Delivery (PD) Charging Specification 2.0 Charging Ports / Amps LED Indicators White (Power), Green (Link), Yellow (Activity) Charging Ports / Amps Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	Product Length (in.)	12	
Product Length (m.) 0.3 BATTERY Battery Charging (5V/1.5A Port) No POWER External Power Supply Output 5V/2A External Power Supply DC Barrel Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging yes USB Power Delivery (PD) Charging Specification 2.0 Charging Ports / ALERTS & CONTEXT LED Indicators White (Power), Green (Link), Yellow (Activity) Charging Ports / Amps Charging Ports / Amps (2) 0.9A; 3A Charging Watts 60	Product Length (cm.)	30.48	
BATTERY Battery Charging (5V/1.5A Port) No POWER External Power Supply Output Specs (V / A) SV/2A Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging Support Yes USB Power Delivery (PD) Charging Specification 2.0 USER INTERFACE, ALERTS & CONTOLS LED Indicators White (Power), Green (Link), Yellow (Activity) CHARGING Charging Ports / Amps (2) 0.9A; 3A Charging Watts 60 PHYSICAL	Product Length (ft.)	1	
Battery Charging (5V/1.5A Port) No POWER External Power Supply Output Specs (V / A) 5V/2A External Power Supply DC Barrel Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging Specification Yes USB Power Delivery (PD) Charging Specification 2.0 USER INTERFACE, ALERTS & CONTRACTORY White (Power), Green (Link), Yellow (Activity) CHARGING (2) 0.9A; 3A Charging Ports / Amps (2) 0.9A; 3A Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	Product Length (m.)	0.3	
POWER External Power Supply Output Specs (V / A) 5V/2A External Power Supply DC Barrel Connector Specs OD: 3.5 × 1.35 × 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging Specification Yes USB Power Delivery (PD) Charging Specification 2.0 USER INTERFACE, ALERTS & CONCLS LED Indicators UB Power Joiners White (Power), Green (Link), Yellow (Activity) Charging Ports / Amps (2) 0.9A; 3A Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	BATTERY		
External Power Supply Output 5V/2A External Power Supply DC Barrel Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging Support Yes USB Power Delivery (PD) Charging Specification 2.0 USER INTERFACE, ALERTS & CONTEXTINE LED Indicators USR INTERFACE, ALERTS & CONTEXTINE Vhite (Power), Green (Link), Yellow (Activity) CHARGING (2) 0.9A; 3A Charging Ports / Amps (2) 0.9A; 3A Charging Watts 60	Battery Charging (5V/1.5A Port)	No	
Specs (V / A) SN2A External Power Supply DC Barrel Connector Specs OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve USB Power Delivery (PD) Charging Specification Yes USB Power Delivery (PD) Charging Specification 2.0 USER INTERFACE, ALERTS & CONTRUCT Ves LED Indicators White (Power), Green (Link), Yellow (Activity) CHARGING (2) 0.9A; 3A Charging Ports / Amps (2) 0.9A; 3A Charging Watts 60	POWER		
USB Power Delivery (PD) Charging Yes USB Power Delivery (PD) Charging 2.0 USER INTERFACE, ALERTS & CONTRACTION OF THE CONTRACTION	External Power Supply Output Specs (V / A)	5V/2A	
Support Tes USB Power Delivery (PD) Charging specification 2.0 USER INTERFACE, ALERTS & CONTROLS LED Indicators White (Power), Green (Link), Yellow (Activity) CHARGING Charging Ports / Amps (2) 0.9A; 3A Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	External Power Supply DC Barrel Connector Specs	OD: 3.5 x 1.35 x 9.5mm, Positive Pin, Negative Sleeve	
Specification 2.0 USER INTERFACE, ALERTS & CONTROLS LED Indicators White (Power), Green (Link), Yellow (Activity) CHARGING Charging Ports / Amps (2) 0.9A; 3A Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	USB Power Delivery (PD) Charging Support	Yes	
LED Indicators White (Power), Green (Link), Yellow (Activity) CHARGING Charging Ports / Amps Charging Ports / Amps (2) 0.9A; 3A Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	USB Power Delivery (PD) Charging Specification	2.0	
CHARGING Charging Ports / Amps (2) 0.9A; 3A Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	USER INTERFACE, ALERTS & CONTROLS		
Charging Ports / Amps (2) 0.9A; 3A Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	LED Indicators	White (Power), Green (Link), Yellow (Activity)	
Charging Ports USB-C: 60W (20V 3A) Power Delivery (PD 2.0) Total Charging Watts 60	CHARGING		
Total Charging Watts 60 PHYSICAL	Charging Ports / Amps	(2) 0.9A; 3A	
PHYSICAL	Charging Ports	USB-C: 60W (20V 3A) Power Delivery (PD 2.0)	
	Total Charging Watts	60	
	PHYSICAL		
Goor Silver	Color	Silver	



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

Cable Jacket Rating VV-1 Material of Construction Auminium Shipping Weigh (fbs.) 0.8 × 70 × 320 Shipping Weigh (fbs.) 0.67 × 4.7 × 2.2 Unit Dimensions (hwd / in.) 0.67 × 4.7 × 2.2 Unit Packaging Type Box Unit Weight (fbs.) 0.10 Unit Weight (fbs.) 0.21 ENVIRONMENTAL Operating Temperature Range 32 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidry 5% to 89% RH, Non-Condensing BTUS 15.7 BTUHr Power Consumption (Watts) 4.6 Power Consumption (Watts) 4.6 Power Consumption (Watts) 4.6 Power Consumption (Watts) 4.6 Power Powided to Connected 5V 0.9A (4.5W) Curput (USB A), Up to 20V 3A (60W) Input (USB C) Commetors 5V 0.9A (4.5W) Curput (USB A), Up to 20V 3A (60W) Input (USB C) Connector B 50 0.9A (4.5W) Curput (USB A), Up to 20V 3A (60W) Input (USB C) Eletter Standards Supported 802.3 Connector S 2 X USB 3.0, MICRO SD, SD, BD, ML R, J4S LAN, USB-C PD CHAR		
Shipping Dimensions (hvd / in.) 0.80 x 5.70 x 3.20 Shipping Weight (bs.) 0.30 Unit Dimensions (hvd / in.) 0.87 x 4.7 x 2.2 Unit Dimensions (hvd / in.) 0.87 x 4.7 x 2.2 Unit Weight (kg.) 0.10 Unit Weight (kg.) 0.110 Unit Weight (kg.) 0.21 ENVIRONMENTAL 0.21 n. Operating Temperature Range 32 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidhy 5% to 55% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Consumption (Watts) 4.6 Power Provided to Connected 5V 0.94 (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS Storage Temperature Range Network Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 1 HDMI (FEMALE) F.H46 (FEMALE) Side B - Connector 2 (2) USB 3.0	Cable Jacket Rating	VW-1
Shipping Weight (Ibs.) 0.30 Unit Dimensions (Iwud / In.) 0.67 x 4.7 x 2.2 Unit Weight (Ibs.) 0.10 Unit Weight (Ibs.) 0.21 ENVIRONMENTAL 0.21 Operating Temperature Range 12 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidity 5% to 95% RH, Non-Condensing BTUa 15.7 BTU/Hr Power Consumption (Watts) 4.6 Power Provided to Connected 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) Connectors 6 Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 Connectors 2 X USB 3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 2 (2 USB 3.0A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5	Material of Construction	Aluminium
Unit Dimensions (twd / in.) 0.67 x 4.7 x 2.2 Unit Packaging Type Box Unit Weight (kg) 0.10 Unit Weight (kg) 0.21 ENVIRONMENTAL Operating Temperature Range 32 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidity 5% to 95% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Provided to Connected 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS 4.6 Power Provided to Connected 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS 4.8 Network Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 CONNECTIONS 8 Dock Connector 1 UBS C (MALE) Side A - Connector 1 UBS C (MALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Cobaccor 7 SD (FEMALE)	Shipping Dimensions (hwd / in.)	0.80 x 5.70 x 3.20
Unit Packaging Type Box Unit Weight (kg) 0.10 Unit Weight (kg) 0.21 ENVIRONMENTAL Operating Temperature Range 32 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidity 5% to 95% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Consumption (Wats) 4.6 Power Provided to Connected Device(s) 5V 0.94 (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS Sto 3.3 COMMUNICATIONS 6/(3gabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 CONNECTIONS 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side A - Connector 1 USB C (MALE) Side B - Connector 3 MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1	Shipping Weight (lbs.)	0.30
Uni Weight (kg) 0.10 Uni Weight (kg) 0.21 ENVIRONMENTAL Operating Temperature Range 32 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidity 5% to 95% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Consumption (Watts) 4.6 Power Consumption (Watts) 4.6 Power Ocnsumption (Watts) 4.6 Power Storage Temperature Range 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS 802.3 CONNECTIONS 802.3 Ports 8 Dock Connector 1 USB C (MALE) Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0.4 (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE)<	Unit Dimensions (hwd / in.)	0.67 x 4.7 x 2.2
Unit Weight (bs.) 0.21 ENVIRONMENTAL Operating Temperature Range 32 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidity 5% to 95% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Consumption (Watts) 4.6 Power Provided to Connected 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS 8 Network Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 CONNECTIONS 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 1 HDMI (FEMALE); RJ45 (FEMALE) Side B - Connector 1 HDMI (FEMALE) Side B - Connector 1 HDMI (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE)	Unit Packaging Type	Box
ENVIRONMENTAL Operating Temperature Range 32 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (10 to 70 C) Relative Humidity 5% to 95% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Consumption (Watts) 4.6 Power Oroxide to Connected 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) Commetry 602.3 CONNECTIONS 802.3 Ports 8 Dock Connector 1 USB C (MALE) Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 7 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector 7	Unit Weight (kg)	0.10
Operating Temperature Range 32 to 131 F (0 to 55 C) Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidity 5% to 95% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Consumption (Watts) 4.6 Power Provided to Connected 5V 0.9A (4.5W) Output (USB A). Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS 603abit Ethermet (10/100/1000) IEEE Standards Supported 802.3 CONSECTONS 2X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0A (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 SD (FEMALE) Side B - Connector 4 SD Fype-C (FEMALE) Side B - Connector 5 SD Fype-C (FEMALE) Side B - Connector 4 SD Fype-C (FEMALE) Side B - Connector 4 SD Fype-C (FEMALE) Side B - Connector 5	Unit Weight (Ibs.)	0.21
Storage Temperature Range 14 to 158 F (-10 to 70 C) Relative Humidity 5% to 95% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Consumption (Watts) 4.6 Power Provided to Connected 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS Ketwork Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 CONNECTIONS 8 Ports 8 Dock Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector 7 SD (FEMALE)	ENVIRONMENTAL	
Relative Humidity 5% to 95% RH, Non-Condensing BTUs 15.7 BTU/Hr Power Consumption (Watts) 4.6 Dower Provided to Connected 5v 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) comMUNICATIONS communication Network Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 connectorons sold.3. Ports 8 Dock Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0.4 (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 7 SD (FEMALE) <td< td=""><td>Operating Temperature Range</td><td>32 to 131 F (0 to 55 C)</td></td<>	Operating Temperature Range	32 to 131 F (0 to 55 C)
BTUs 15.7 BTU/Hr Power Consumption (Watts) 4.6 Power Provided to Connected 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS Sto 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) Network Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 80.3 CONNECTIONS 8 Ports 8 Dock Connector 1 USB C (MALE) Side A - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Features & SPECIFICATIONS Nickel	Storage Temperature Range	14 to 158 F (-10 to 70 C)
Power Consumption (Watts) 4.6 Power Consumption (Watts) 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS Communications Network Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 CONNECTIONS Volume (USB C) Ports 8 Dock Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE)	Relative Humidity	5% to 95% RH, Non-Condensing
Power Provided to Connected Device(s) 5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C) COMMUNICATIONS Gigabit Ethernet (10/100/1000) Network Speed Gigabit Ethernet (10/100/000) IEEE Standards Supported 802.3 CONNECTIONS Volume Ports 8 Dock Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector 5 USB Type-C (FEMALE) FEATURES & SPECIFICATIONS Nickel	BTUs	15.7 BTU/Hr
Device(s) SV 0.5X (4.5.W) Subject (05.0 X), Op 10 200 SA (00.W) Inplat (05.0 C) COMMUNICATIONS Network Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 CONNECTIONS SV 0.58 (MS.W) Subject (05.0 X), Op 10 200 SA (00.W) Inplat (05.0 C) Ports 8 Dock Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector 5 USB Type-C (FEMALE) HDCP Specification 2.2	Power Consumption (Watts)	4.6
Network Speed Gigabit Ethernet (10/100/1000) IEEE Standards Supported 802.3 CONNECTIONS Ethernet (10/100/1000) Ports 8 Dock Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 1 USB C (MALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) HDCP Specification 2.2		5V 0.9A (4.5W) Output (USB A), Up to 20V 3A (60W) Input (USB C)
IEEE Standards Supported 802.3 CONNECTIONS 8 Ports 8 Dock Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 1 HDMI (FEMALE); RJ45 (FEMALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) HDCP Specification 2.2	COMMUNICATIONS	
CONNECTIONS Ports 8 Dock Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 1 HDMI (FEMALE); RJ45 (FEMALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS HDCP Specification 2.2	Network Speed	Gigabit Ethernet (10/100/1000)
Ports 8 Dock Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 1 HDMI (FEMALE); RJ45 (FEMALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS HDCP Specification 2.2	IEEE Standards Supported	802.3
Dock Connectors 2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA Side A - Connector 1 USB C (MALE) Side B - Connector 1 HDMI (FEMALE); RJ45 (FEMALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) HDCP Specification 2.2	CONNECTIONS	
Side A - Connector 1 USB C (MALE) Side B - Connector 1 HDMI (FEMALE); RJ45 (FEMALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS HDCP Specification 2.2	Ports	8
Side B - Connector 1 HDMI (FEMALE); RJ45 (FEMALE) Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS HDCP Specification 2.2	Dock Connectors	2 X USB3.0A, MICRO SD, SD, HDMI, RJ45 LAN, USB-C PD CHARGING/DATA
Side B - Connector 2 (2) USB 3.0 A (FEMALE) Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector Plating Nickel	Side A - Connector 1	USB C (MALE)
Side B - Connector 3 MICRO SD (FEMALE) Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS HDCP Specification 2.2	Side B - Connector 1	HDMI (FEMALE); RJ45 (FEMALE)
Side B - Connector 4 SD (FEMALE) Side B - Connector 5 USB Type-C (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS HDCP Specification 2.2	Side B - Connector 2	(2) USB 3.0 A (FEMALE)
Side B - Connector 5 USB Type-C (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS HDCP Specification 2.2	Side B - Connector 3	MICRO SD (FEMALE)
Connector Plating Nickel FEATURES & SPECIFICATIONS 2.2	Side B - Connector 4	SD (FEMALE)
FEATURES & SPECIFICATIONS HDCP Specification 2.2	Side B - Connector 5	USB Type-C (FEMALE)
HDCP Specification 2.2	Connector Plating	Nickel
	FEATURES & SPECIFICATIONS	
USB Hub Ports Yes	HDCP Specification	2.2
	USB Hub Ports	Yes
Number of USB Hub Ports 2	Number of USB Hub Ports	2



USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required	No	
Recommended Category Cable	Cat5/5e/6 Cables	
Auto MDIX Support	Yes	
Full Duplex Support	Yes	
Suspend Mode Support	Yes	
Remote Wakeup Support	Yes	
SD Card Specification	SD; Micro SD	
STANDARDS & COMPLIANCE		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies