

Electronic housing - DCS 15 M C O S C 7035 - 2203191

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Display housing, 15", light gray, central window, front level, with cutout for connection technology angle plate consisting of two half shells with screws

Your advantages

- ☑ Display housings for mobile and stationary operator panels
- ☑ Degree of protection: up to IP54
- ▼ Temperature range: -20°C to +50°C
- ▼ Flammability rating UL 94-V0



Key Commercial Data

Packing unit	4 pc
GTIN	4 055626 378459
GTIN	4055626378459

Technical data

Item properties

Туре	DCS 15 M C O S C 7035
Order No.	2203191
Housing type	Display housing
Battery compartment	no
Wall fastening	no
Ventilation openings present	no

Measurements

Width [w]	362 mm
Height [h]	286 mm



Electronic housing - DCS 15 M C O S C 7035 - 2203191

Technical data

Measurements

Depth [d]	62 mm	
Material specifications		
Flammability rating according to UL 94	V0	
Housing material	ABS	
Packaging information		
Pieces per package	4	
Denomination packing units	Pcs.	
Standards and regulations		
Flammability rating according to UL 94	V0	

Phoenix Contact 2019 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com