

This document was generated on 12/15/2017

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0945294102

Status: Active

Description: 5.00mm Pitch RAST, Receptacle, Natural Color, PA Polyamide (Nylon) 6/6, 2 Circuits,

Glow Wire Capable

**Documents:** 

<u>3D Model</u> <u>Product Specification PS-94529-002-001 (PDF)</u>
Drawing (PDF) Application Specification AS-45499-001-001 (PDF)

Product Specification PS-94529-001-001 (PDF) RoHS Certificate of Compliance (PDF)

General

Product Family Crimp Housings

Series 94529

Application Power, Wire-to-Board

Comments This Molex product is manufactured from material

that has the following ratings, tested by independent agencies :. a) A Glow Wire Ignition Temperature (GWIT) of at least 775 deg C per IEC 60695-2-13.. b) A Glow Wire Flammability Index (GWFI) above 850 deg C per IEC 60695-2-12.and hence complies with the requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical appliances - safety; section 30 Resistance to heat and fire.<P><P>The customers using this product must determine its suitability for use in their particular application through testing or other acceptable means as described in end-product glow-wire flammability test standard IEC 60695-2-11 and any applicable product end-use standard(s).<P>If it is determined during the customer's evaluation of suitability, that higher performance is required, please contact Molex for

possible product options.

RAST 5

PC 822350324373

UPC

**Physical** 

**Product Name** 

Breakaway No
Circuits (maximum) 2
Color - Resin Natural
Gender Receptacle

**Glow-Wire Compliant** Yes Lock to Mating Part Yes Material - Resin Nylon Net Weight 1.035/qNumber of Rows Packaging Type Bag Panel Mount No Pitch - Mating Interface 5.00mm Pitch - Termination Interface 5.00mm Polarized to Mating Part Yes **Ports** 


Temperature Range - Operating -40°C to +105°C, -40°C to +85°C

Nο

**Electrical** 

Stackable

Current - Maximum per Contact 6.0A



## EU ELV

Compliant

EU RoHS China RoHS

Compliant

**REACH SVHC** 

Not Contained Per - ED/30/2017 (7 July

2017)

**Halogen-Free** 

Status

**Not Low-Halogen** 

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Not Relevant
ELV Compliant
RoHS Phthalates Not Contained

Search Parts in this Series

94529 Series

Mates With

PCB thickness 1.50mm

**Use With** 

94529-1203 Terminal

## **Material Info**

Reference - Drawing Numbers
Application Specification
Product Specification
Sales Drawing

AS-45499-001-001 PS-94529-001-001, PS-94529-002-001 SD-94529-004

This document was generated on 12/15/2017

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION