



**NOTES:** UNLESS OTHERWISE SPECIFIED

1. ALL RES. ARE IN OHMS, 5%.
2. ALL CAP. ARE CERAMIC AND IN MICROFARADS.
3. INSTALL SHUNTS ON JP1-JP3 PIN 1 AND 2.

<p><b>CONFIDENTIAL INFORMATION</b></p> <p>THIS DOCUMENT CONTAINS UNPUBLISHED INFORMATION WHICH IS PROPRIETARY TO AND IS THE PROPERTY OF LINEAR TECH. CORP. AND MAY NOT BE USED, DISCLOSED OR REPRODUCED WITHOUT THE EXPRESS WRITTEN PERMISSION OF LINEAR TECH. CORP.</p> <p>TRADE SECRET INFO.</p>		<p>APPROVALS</p> <p>DRAFTER: KIM TRAN</p> <p>CHECKER:</p> <p>ENGR.: MGR</p> <p>PROJ.: DIR</p> <p>NEXT ASSEMBLY:</p> <p>ASSY-</p>		<p>DATE</p>
		<p><b>LINEAR TECHNOLOGY CORP</b></p> <p>1630 MCCARTHY BLVD. MILPITAS, CA 95035 PH. (408) 954-8400 FAX (408) 434-0507</p>		<p>Sheet 1 of 1</p>
<p>Title</p> <p><b>2A CC/CV BATTERY CHARGER</b></p>		<p>Document Number</p> <p><b>DC243A-1*LT1769CGN</b></p>	<p>Rev</p> <p><b>A</b></p>	<p>Date: Friday, January 31, 2003</p>