

Tripp Lite
1111 W. 35th Street

Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

400G Multimode 50/125 OM4 Plenum Fiber Optic Cable, 16F MTP/MPO-APC to 24F MTP/MPO-UPC (F/F), Magenta, 1 m

MODEL NUMBER: N846D-01M-16CMG











400 GbE Ethernet cable supports high bandwidths necessary for next-generation cloud services, hyperscale data centers and telecom carriers.

Features

400 GbE Cable Supports Higher Bandwidths Needed for Next-Gen Data and Voice Networking
As the amount of traffic in data networks grows, so does the need for next-generation devices and fiber
cables to support much higher bandwidths in cloud services, hyperscale data centers, telecom
applications and equipment OEM companies. This multimode 50/125 OM4 cable is an ideal choice for
400G Ethernet applications up to 100 meters (at 850 nm). It has documented insertion loss and back
reflection testing on every connector and attenuation loss that meets or exceeds current standards.

16-Fiber and 24-Fiber MTP/MPO Connectors Designed for the Latest QSFP-DD Transceivers
The MPO connectors have a wide parallel optical interface for use with the latest 400G QSFP-DD
transceivers, making this cable an excellent solution for your high-density network application. The
connectors are the same size as standard SC connectors, but 12 times denser, allowing vertical stacking
in switches or patch panels where space is at a premium. Pull tabs make the cable easy to install or
remove with one hand.

Magenta Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The OM4-rated cable has a magenta jacket, which is easy to identify quickly in a crowded patch panel or switch and helps prevent the cable from becoming accidentally disconnected. The three-millimeter ruggedized plenum-rated jacket has low smoke and flame characteristics, making it suitable for premise applications in ceilings, walls and ducts.

Specifications

OVERVIEW	
UPC Code	037332258311
Technology	Multimode

Highlights

- OM4-rated cable recommended for 400 Gb speeds up to 100 m (@ 850 nm)
- MTP/MPO 16- and 24-fiber ends designed for next-gen 400G QSFP-DD transceivers
- Connectors tested for low insertion loss and back reflection to ensure top performance
- Plenum rated for horizontal premise applications in air ducts and drop ceilings
- Magenta jacket allows fast, easy identification in a crowded switch or patch panel

Applications

- Connect 400G fiber Ethernet networks in your cloud service, hyperscale data center or telecom application
- Connect 400G Cisco, Arista, Juniper and other network switches through air ducts and drop ceilings

Package Includes

N846D-01M-16CMG 400G Multimode 50/125 OM4 Fiber Optic Cable, Magenta, 1 m





Optical Mode	OM4	
PHYSICAL		
Cable Jacket Color	Magenta	
Cable Jacket Material	PVC	
Cable Jacket Rating	OFNP	
Clad Diameter (microns)	125	
Core Diameter (microns)	50	
· · · · ·	245	
Primary Coating Diameter (microns)		
Number of Fibers	16	
Cable Length (ft.)	3.3	
Cable Length (m)	1.01	
Cable Length (in.)	39.4	
Minimum Bend Radius	20MM (Dynamic); 10MM (Static)	
ENVIRONMENTAL		
Operating Temperature Range	-4 to 140 °F (-20 to 60 °C)	
Storage Temperature Range	-4 to 140 °F (-20 to 60 °C)	
Operating Humidity Range	5% to 85% RH, Non-Condensing	
Storage Humidity Range	35% to 65% RH, Non-Condensing	
COMMUNICATIONS		
Network Compatibility	10 Gbps; 40 Gbps; 100 Gbps; 400 Gbps; 800 Gbps	
Transmission Distance	100M @ 850NM WAVELENGTH	
Attenuation @ 850NM	3.0dB/Km	
Insertion Loss	16F: 0.60dB; 24F: 0.35dB	
CONNECTIONS		
Side A - Connector 1	16-STRAND MTP/MPO (FEMALE)	
Side B - Connector 1	24-STRAND MTP/MPO (FEMALE)	
Endface Polish	APC; UPC	
Connector Color	Green; Black; Aqua	
FEATURES & SPECIFICATIONS		
Push/Pull Tabs	No	
Breakout	No	
Trunk	No	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

OTANDADDO A COMPLIANOS		
STANDARDS & COMPLIANCE		
Certifications	RoHS, REACH	
Approvals	RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies