



NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

THERMOPLASTIC POLYESTER, UL94V-0 STEEL, NICKEL PLATED COPPER ALLOY, GOLD FLASH PLATING

OPERATING TEMPERATURE: -55°C TO +85°C

CURRENT RATING:3A PER CONTACTCONTACT RESISTANCE:25mΩ MAX.INSULATOR RESISTANCE:5000MΩ min.DIELECTRICWITHSTANDING VOLTAGE:1000V AC rms

SW REFERENCE NO.: 622 ASSEMBLY DRAWN: C.B DATE: AUG. 01/2018 CHECKED: DATE: CHECKED: DATE: NS SCALE: (IN C.A.D. 1:1) SHEET 1 OF 1 US DRAWING NUMBER: 622-025-260-011 ISSUE 1				
DATE: CHECKED: DATE: D SCALE: UB DRAWING NUMBER: 622-025-260-011 ISSUE		SW REFERENCE NO.: 622 ASSEMBLY		
NS SCALE: (IN C.A.D. 1:1) SHEET 1 OF 1 IED DRAWING NUMBER: 622-025-260-011 ISSUE 1		DRAWN: C.B	DATE: AUG. 01/20	018
DRAWING NUMBER: 622-025-260-011 ISSUE		CHECKED:	DATE:	
US DRAWING NUMBER: 622-025-260-011 ISSUE	D IED	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	1
		DRAWING NUMBER: 622-025-2	260-011	ISSUE
		PART NUMBER: 622-025-2	260-011	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.



622 SERIES D-SUB CONNECTOR

THESE DRAWINGS AND SPECIFICATION ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIE OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATU WITHOUT WRITTEN PERMISSION.