E	m m		0	₿ >	
Z'	ØS				
۵			LAYOUT SHOWN AS EXAM	PLE	
	Keying Shown as example				
 CHARACTERISTICS Standard : Based on MIL-DTL-38999 Series III Shell Material : Composite Shell Plating : Olive drab Cadmium Insulator : Thermoplastic Contacts : Copper Alloy Seals & Grommet : Silicon Elastomer Contact Plating : Gold over copper Alloy 0.8µm minimum Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories Temperature Range : -65°C to +175°C 	Connector dimensionDimNominalØS25 MaxZ'31.5 MaxVV THREADM15x1-6g	A 15-10-2016 F	SOURIAU shall not be liable for any nor due to a use of the Products which of the Specifications issued by either of the (professional recommendation, Country FR PN: 8D511J01	loes not comply with Parties or by a third party technical notice.) Jurisdiction & Control List Not Listed	
-Salt Spray : 2000 hours 		ISS DATE Designed By:	Latest modification - by Date:	CUSTOMER DRAWING	DD N°
		TITLE		e Plug 8D series	
SHELL TYPE : Plug with RFI Shielding CONTACT TYPE : Standard Crimp Contact	J 01 P D ORIENT. CONTACT TYPE : PIN(500	ATION : D Matings)	General linear Tolerances: ± WWW.SOURIAU.CON	communicated without permission	
SHELL SIZE : 11		IT · 11_01 FORMAT		RG N° SH	HEET

	 τ	G)	П		т		D	0	
		Contact Layout								
4		01								
	[1#12		1						
ى	Ctc A	11-01 X 0	Y 0							
									SOURIAU shall not be due to a use of the the Specifications issue (professional r	e Products wh d by either of
N										Countr FR
								A 15-10-202 ISS DATE	PN: 16 First Release Latest modification - by	8D511.
								Designed By:	Date:	Compo
_ _								SCALE NA		eneral linear Tolerances: ±
								FORMAT		URIAU.C
				-	I		7	A3	3	3D511J(
	Н	G		F		E	\bigvee	D	С	

