

OPERATING TEMPERATURE: -55°C TO +85°C

CURRENT RATING: CONTACT RESISTANCE: $25m\Omega$ MAX. **INSULATOR RESISTANCE:** 5000MΩ min. DIELECTRIC

3A PER CONTACT

WITHSTANDING VOLTAGE: 1000V AC rms

	622 SERIES D-SUB CONNECTOR		SW REFERENCE NO.: 622 ASSEMBLY		
			DRAWN: C.B	DATE: AUG. 01/20)18
			CHECKED:	DATE:	
	EDAC INC TORONTO, ONTARIO CANADA YOUR CONNECTION TO QUALITY & SERVICE	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	SCALE: (IN C.A.D. 1:1)	SHEET 1 OF	1
			DRAWING NUMBER: 622-037-668-011		ISSUE
			PART NUMBER: 622-037-6	668-011	1



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.