



Product: <u>633938</u> ☑

Surveillance CATV MATV, RG-6 #18 Sol BC, FFEP Core, Duofoil® + AL Braid, Flamarrest® Jkt, CMP, CATVP

Product Description

Surveillance, CATV & MATV, RG6, 18 AWG solid bare copper, foam FEP core, Duofoil® + 90% aluminum braid, Low Smoke PVC jacket, CMP & CATVP

Technical Specifications

Product Overview

FIOU									
Suitab	le Applicat	ions:		CA	TV, MA	TV			
Cons	Construction Details								
RG Type: 6									
	P0.			Ŭ					
Conductor									
Size	Stran	ding	Nom	. Diameter	neter Material				
18 AW	G Solid		0.040) in	BC - E	Bare Copper			
Insulat	ion								
insulat		Mat	erial			Nom. Insulat	ion Diamoter	Color	do
EED	Eluorineta			Bropylone (Foom	0.170 in (4.32		Code	
FEP -	FIUOIINAte	u Etni	yiene	Propylene (roam)	0.170 IN (4.32		White	
Outer S	Shield								
Layer	Outer SI	nield	Туре		Mater	ial	Material Tra	de Name	Coverage
1	Tape			Tri-Lamina	te (Alu	m+Poly+Alum)	Duofoil®		100%
2	Braid			Aluminum					90%
0									
Outer J									
	Material			Nom. Diam					
PVC -	PVC - Polyvinyl Chloride 0.233 in (5.92 mm)								
Overa	Overall Cable Diameter (Nominal): 0.233 in (5.92 mm)								
Floct	Electrical Characteristics								
FIECI									

Attenuation

Frequency	Nom. Attenuation
1 MHz	0.24 dB/100ft
3 MHz	0.45 dB/100ft
5 MHz	0.55 dB/100ft
8 MHz	0.70 dB/100ft
10 MHz	0.85 dB/100ft
50 MHz	1.50 dB/100ft
100 MHz	2.10 dB/100ft
200 MHz	3.10 dB/100ft
400 MHz	4.50 dB/100ft
700 MHz	6.00 dB/100ft
900 MHz	6.90 dB/100ft
1000 MHz	7.30 dB/100ft

Electricals

Nom. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
6.4 Ohm/1000ft	3.5 Ohm/1000ft (11 Ohm/km)	16.3 pF/ft (53.5 pF/m)	75 Ohm	83%

Voltage

UL Voltage Rating

300 V (CMP)

Mechanical Characteristics

Temperature

UL Temperature	Operating			
75°C	-20°C to +75°C			

Bend Radius

Installation Min.	
2.3 in (58 mm)	
Max. Pull Tension:	104 lbs (47.2 kg)
Bulk Cable Weight:	28 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor - Plenum, Indoor
Sustainability:	CA Prop 65, Product Lens™, Environmental Product Declaration (EPD) Available
Flammability / Reaction to Fire:	NFPA 262
NEC / UL Compliance:	CATVP, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.469 Revision Date: 05-25-2023

Part Numbers

Variants

	ltem #	Color	Putup Type	Length	UPC
	633938 010U1000	Black	UnReel	1,000 ft	612825176091
	633938 008U1000	Gray	UnReel	1,000 ft	612825176077
	633938 877500	Natural	Reel	500 ft	612825176121
	633938 8771000	Natural	Reel	1,000 ft	612825176114
	633938 877U1000	Natural	UnReel	1,000 ft	612825176107
	633938 009U1000	White	UnReel	1,000 ft	612825176084

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.