1	т <u></u>	т	D	0	Ξ	A	_	
4							4	
ω				LAYOUT SHOWN AS E	EXAMPLE		3	
	Keying Sho	own as example						
	CHARACTERISTICS	Connector dimension						
	Standard : Based on MIL-DTL-38999 Series III	Dim Nominal						
2	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum	ØS25 MaxZ31 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.) Country Jurisdiction & Control List FR Not Listed				
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D511W01BN				
	-Temperature Range -65°C to +175°C		A 17-10-2016	First Release				
	-Salt Spray : 500 hours -Mass : 17.92 g ± 10%		ISS DATE	Latest modification - by		MOD N°	•	
			Designed By:	Date:	CUST	OMER DRAWING		
			TITLE	TITLE Aluminium Plug 8D series				
_	BASIC SERIES: 8D 5 - 11 W 01 B N SHELL TYPE : Plug with RFI Shielding		SCALE	General linear Tolerances:		RDS / PROJECT 859	1	
	CONTACT TYPE : Standard Crimp Contact ORIENTATION			SOURIAU This document is the property of SOURIAU it must not be reproduced or communicated without permission				
	SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 11-01			SOURIAU		SHEET		
			A3	8D511W		1/2		
				0001100		1	1	

F	Ŧ	G	ات	m	D	0
		Contact Layout				
4	/	01				
_	(1#12				
	Ctc A	11-01 X Y 0 0				
ω						
	_					SOURIAL chall not be liable for an
						SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either of (professional recommendat
C)						PN: 8D511V
					A 17-10-2 ISS DATE	016 First Release
					Designed By:	Date: Alumin
<u> </u>					SCALE NA	General linear Tolerances:
					FORMAT	U WWW.SOURIAU.C SOURIAU
					A3	8D511W
	Н	G	F	E	D	C

