NSYSM1410402DP

Spacial SM compact enclosure with mounting plate - 1400x1000x400 mm

Green Premium™ Product

Main

Range	Spacial
Product name	Spacial SM
Product or Component Type	Compact enclosure
Application	Multi-purpose
Installation accessory type	Floor-standing
Device composition	1 body 2 door 1 cable gland plate 1 locking system with handle door 1 blocking system left door 4 mounting plate bracket 1 mounting plate
Removable parts	Door by screws hinge Mounting plate by screws mounting plate bracket Mounting plate bracket by screws
Enclosure nominal height	55.12 in (1400 mm)
Enclosure nominal width	39.37 in (1000 mm)
Enclosure nominal depth	15.75 in (400 mm)

Complementary

Number of doors	Front 2
Door opening side	Left 120 °) Right 120 °)
Door type	Solid
Lock type	4 points lock, handle with 5 mm double bar insert
Body type	Single piece body with welded rear panel Front part forming a rigid frame with welded corners
Mounting plate description	Plain
Type of gland plate	Standard
Cable entry	1 entry
Material	Mounting plate galvanised steel Body sheet steel Door sheet steel Hinge zamak
Surface finish	Epoxy-polyester powder
Color	Enclosure Gray RAL 7035) Handle Black RAL 9005)
Accessibility for operation	Front
Net Weight	229.28 lb(US) (104 kg)

Environment

Standards	IEC 62208
Product Certifications	DNV BV UL
IK degree of protection	IK10 IEC 62262
IP degree of protection	IP55 IEC 60529

Jul 13, 2022

Life Is On | Schneider Electric

Ordering and shipping details

Category	80035-ENCLOSURE SYSTEMS FLOOR MOUNT
Discount Schedule	ES1
GTIN	03606485120089
Nbr. of units in pkg.	1
Package weight(Lbs)	229.28 lb(US) (104.0 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	60.24 in (153.0 cm)
Package 1 width	41.14 in (104.5 cm)
Package 1 Length	19.29 in (49.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months