Data Sheet

Coaxial Panel Connector 22_QN-50-0-1/133_N

Description

Straight bulkhead receptacle jack

Interface standards QN QLF compliant



Technical Data

Electrical Data		
Impedance	50 Ω	
Interface frequency max.	11 GHz	
Mechanical Data		
Number of matings	100	
Weight	0.012 kg	
Environmental Data		
Operating temperature	-40 °C to 125 °C	
2011/65/EU (RoHS - including	compliant	
2015/863 and 2017/2102)		
Material Data		
Piece Parts	Material	Surface Plating
Centre contact	Bronze	SUCOPRO Plating
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Related Documents		
Outline drawing	DOU-00010244	
Catalogue drawing	DCA-00010246	
Ordering Information		
Tray package	22_QN-50-0-1/133_NY	

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

HUBER+SUHNER