

Specification Sheet

Part Number: 596-00890

Made with UV-stable inks and materials for durability and weather

resistance.

Reflective properties to meet applicable NEC code requirements for

reflective identification.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

RAPID SHUTDOWN SWITCH FOR SOLAR PV SYSTEM

Solar Label, Reflective, PHOTOVOLTAIC SYSTEM...SHUTDOWN, 6.5" x 1.0", VL, Red, 10/pkg

Article Number 596-00890

Type PSEWRS1710

Color Red (RD)

Quantity Per pack

Product Description	HellermannTyton makes it easier than ever for solar installers to meet PV labeling codes. Solar Label Convenience Packs allow installers to quickly and economically purchase high quality preprinted NEC code-compliant solar installation labels. Packaged in 10-count quantities to meet the needs of smaller scale solar installations and independent contractors, Solar Label Convenience Packs are available in HellermannTyton's most popular preprinted NEC code-compliant solar label formats. Each Solar Label Convenience Pack contains 10 solar installation labels. Choose from a variety of regular and reflective preprinted labels. For enhanced durability, clear laminate overlay labels are also available in a convenience pack.
Short Description	Solar Label, Reflective, PHOTOVOLTAIC SYSTEMSHUTDOWN, 6.5" x 1.0", VL, Red, 10/pkg
Global Part Name	PSEWRS1710-505/281-RD
Length L (Imperial)	1.0
Length L (Metric)	25.4
Width W (Imperial)	6.5
Width W (Metric)	165.1
Thickness T (Imperial)	0.0025

64.0

1.0

25.40

Thickness T (Metric)

Height H (Imperial)

Height H (Metric)

Material	Type 505/281, UV-stabilised, reflective vinyl with clear polyester laminate (505/281)
Material Shortcut	505/281
Adhesive	Acrylic
Halogen Free	No
UV Resistant (Yes/No)	Yes
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification Warranty (US)	UL 969 NEC2017 NEC2023 NEC2020 Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	3919905060

1

Labels per Column

