т	Q	н п		0







LAYOUT SHOWN AS

Keying Shown as example

CHARACTERISTICS

ယ

 \sim

-Mass

BASIC SERIES:

SHELL SIZE : 17

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

PLATING : J = Olive drab Cadmium

-Standard : Based on MIL-DTL-38999 Series III

ł	-Shell Material	: Composite		
	-Shell Plating	: Olive drab Cadmium		
	-Insulator	: Thermoplastic		
	-Contacts	: Copper Alloy		
	-Seals & Grommet	: Silicon Elastomer		
	-Contact Plating	: Gold over copper Alloy $0.8 \mu m$ minimum		
	-Durability	: 500 Mating cycles		
	-Delivered without Sou	Delivered without Souriau contacts		
	-Temperature Range	: -65°C to +175°C		
	-Salt Spray	: 2000 hours		

: 19.6 g ± 10%

8D 0

G

17

J

75

Ρ

F

В

L

Connector dimension		
Nominal		
3.25±0.2		
4.93±0.2		
26.97		
24.61		
33.3±0.3		
19.5+1.4/-0		
2.1/3.65		
32 Max		
M25x1-6g		

Delivered W/O Contacts


CONTACT LAYOUT : 17-75

CONTACT TYPE : PIN(500 Matings)

Е

ORIENTATION : B

SOURIAU shall not be liable for due to a use of the Products the Specifications issued by either (professional recommend



Φ		A		
Co Cat			4	
	3			
S EXAMPLE			3	
any non-conformi which does not co of the Parties or l ndation, technical n	mply with by a third party			
Intry Juriso	liction & Control Not Listed	List	2	
7J75PBL				
	CUSTOMER DF			
site Receptacle 8D series				
ar	NPRDS / PRO	OJECT		
	859 This docume	ent is the property of	1	
This document is the property of SOURIAU it must not be reproduced or communicated without permission				
U DRG N° SHEET				
J75PBL-C		A 1/2		
5	I			

	Ŧ	ര	וד-	m	D	0
		Contact Layout 75				Panel Cut SQUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING R1
4					λ Σ	
	Ctc A	2#8 Triax 17-75 X Y 0 4.75			<u>,</u>	Max. thickness panel for receptacle: Type 0: front n
ω	В	0 -4.75				Dim ØA ØAA R1 ØT
	-					
						SOURIAU shall not be liable for a due to a use of the Products the Specifications issued by either (professional recommend
N						PN: 8D017
					B 10-04- ISS DATE Designed By:	Date:
					SCALE NA	Composi General linear Tolerances: ±
					FORMAT	WWW.SOURIAU
	Н	G	F	E	A3	8D017J
	11	, U	ı I			

