	D I	т п		C 0		
4	Z M Thread	ØF George Contraction of the second s				4
ယ		Keying Shown as example		LAYOUT SHOWN AS EXAMPLE		3
		Connector dimension Dim Nominal	7			
N	-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories	F22.25 MaxZ31.5 MaxVV THREADM18x1-6g		SOURIAU shall not be liable for any non-con- due to a use of the Products which does r the Specifications issued by either of the Partie (professional recommendation, techn <u>Country</u> FR <b>PN: 8D113F98BA</b>	not comply with es or by a third party ical notice.) Jurisdiction & Control List Not Listed	2
	-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours		A 27-09-	-2016 First Release		
			ISS DA Designed By:	TE Latest modification - by Date:	MOD N CUSTOMER DRAWING	· · · · · · · · · · · · · · · · · · ·
			TITLE	Aluminium Inline	plug 8D series	
<u> </u>	BASIC SERIES:8D1-13FSHELL TYPE : In line Receptacle </td <td>98 B A</td> <td>SCALE NA</td> <td>General linear Tolerances: ±</td> <td>NPRDS / PROJECT <b>859</b></td> <td>1</td>	98 B A	SCALE NA	General linear Tolerances: ±	NPRDS / PROJECT <b>859</b>	1
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13	ORIE CONTACT TYPE : SOCKET(5	NTATION : A SOURI	AU WWW.SOURIAU.COM	This document is the property of SOURIAU it must not be reproduced or communicated without permission	
	PLATING : F = Nickel	CONTACT LAY	YOUT : 13-98 FORMAT	SOURIAU DRG 8D113F98BA-		
L	H G	F E	D	C B	A	

	Т	Q	<del>ال</del> -	ш		0	Φ	Þ	
		Contact Layout							
4	×	$ \begin{array}{c} & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & $							4
	Conta position A B C C D E F G G H	(1111)         (1111)           +.000 (0.00)         +.195 (4.95)           +.125 (3.18)         +.150 (3.81)           +.133 (4.90)         +.030 (0.76)          104 (4.17)        105 (2.07)           +.000 (0.00)        135 (3.43)          164 (4.17)        105 (2.67)          193 (4.90)         +.030 (0.76)          125 (3.18)         +.150 (3.81)							
ω	size no. co								3
	_					due to a use of the Pro	le for any non-conformity or da ducts which does not comply v	vith	
							either of the Parties or by a th nmendation, technical notice.) Country Jurisdiction	& Control List	
N						PN: 80	FR Not 113F98BA	Listed	2
					ISS DATE	First Release Latest modification - by		MOD	 N°
					Designed By:	Date:	ninium Inline plug 8D	TOMER DRAWING Series	
-					SCALE -{	Genera Tolera ±	ances:	PRDS / PROJECT <b>859</b> This document is the property of	1
					FORMAT		IAU.COM	SOURIAU it must not be reproduced or ommunicated without permission	
				I	A3		RIAU DRG N° L13F98BA-C	SHE 2/2	
L	Н	G	F	E	D	C	В	A	