	T	ם ד	1	т	D	0	σ	A		
4		ØS De autorial de la competition de la competit							4	
ω						LAYO	OUT SHOWN AS EXAMPLE		3	
	CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal									
	ØS 35.7 Max Shell Material : Composite Shell Plating : Nickel Insulator : Thermoplastic Contacts : Copper Alloy					SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper A	Alloy 0.8µm minimum					Country Juris FR	diction & Control List Not Listed	2	
	-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +200°C -Salt Spray : 2000 hours					PN: 8D517M06BE				
						A 17-10-2016 First Release				
	-Mass : 35.5 g ± 10%				ISS DATI Designed By:	E Latest modification Date:	н - by	MOD N CUSTOMER DRAWING	• 	
						TITLE Composite Plug 8D series				
	BASIC SERIES: 8D SHELL TYPE : Plug with RFI Shielding	5 - 17 M 06	BE		SCALE NA		General linear Tolerances: ±	NPRDS / PROJECT 859		
	CONTACT TYPE : Standard Crimp Contact ORIENTATION : E					U WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or				
	SHELL SIZE : 17 CONTACT TYPE : SOCKET(500 Matings) PLATING : M = Nickel CONTACT LAYOUT : 17-06					communicated without permission SOURIAU DRG N° SH				
	Н	GF		F	A3	С	8D517M06BE-C	Δ		
			I		D					

Г	T G	т	п		0	σ	A		
	Contact Layout								
4	+Y								4
	$-x \left(\begin{array}{c} E \\ \bigoplus \\ D \\ \bigoplus \\ F \\ \bigoplus \\ \bigoplus \\ \bigoplus \\ \bigoplus \\ B \\ \oplus \\ B \\ \end{array} \right) + x$								
	$\begin{array}{cccc} -x & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & &$								
_	Contacts (Insert arrangement 17-6)							-	
	Contact position ID Location X-axis Y-axis (mm) (mm) A +.121 (3.07) +.209 (5.31) B +.241 (6.12) +.000 (0.00)								
ω	B -2.24 (6.12) -0.00 (0.00) C +.000 (0.00) -241 (6.12) D 241 (6.12) +.000 (0.00) E 121 (3.07) +.209 (5.31) F +.000 (0.00) +.000 (0.00)								3
		rsedes 1053-6							J
					due to a use of the Pro the Specifications issued by	le for any non-conformity or da ducts which does not comply w either of the Parties or by a thi	vith ird party		
					(professional recor	nmendation, technical notice.)			
N					FR Not Listed				2
					PN: 8D517M06BE				
				A 17-10-2016 ISS DATE	First Release Latest modification - by			MOD N°	
				Designed By:	Date:	CUS	TOMER DRAWING		
				TITLE	TITLE Composite Plug 8D series				
_				SCALE -{	Genera Tolera		PRDS / PROJECT 859		1
					SOURIAU This document is the prope SOURIAU SOURIAU it must not be reproduced communicated without permitting				1
				FORMAT		RIAU DRG N°		SHEET	
L	H G	E	E	A3	8D5 C	17M06BE-C	A	2/2	
		I F			U	D	I A		