



ERK610Z392KQH0

Aliases (C817QH392K440XV761, ERK610RK4390KQH0) Obsolete

ERK610 SFTY X1-440 Y2-300, Ceramic, 3900 pF, 10%, 440 VAC (X1), 300 VAC (Y2), Y5U, Lead Spacing = 12.5mm





(1) - Coating on lead (2) - Point of support shall not extend below on printed cardboard. this line.

Click here for the 3D model.

Dimensions	
D	13.5mm MAX
Н	3.3mm +/-0.3mm
Т	4.5mm MAX
S	12.5mm NOM
LL	3.5mm MIN
F	0.8mm +/-0.05mm
А	7mm +/-1.5mm
V	1.6mm +/-0.5mm

Packaging Specifications

Packaging

Bulk, Bag

General Information		
Series	ERK610 SFTY X1-440 Y2-300	
Style	Radial Disc	
Description	Ceramic Single Layer Safety Disc Capacitors	
RoHS	Yes	
Termination	Tin	
Qualifications	UL, CSA, CAN, ENEC, VDE	
AEC-Q200	No	

Specifications			
Capacitance	3900 pF		
Capacitance Tolerance	10%		
Voltage AC	440 VAC (X1), 300 VAC (Y2)		
Temperature Range	-40/+125°C		
Temperature Coefficient	Y5U		
Dissipation Factor	2.5%		
Insulation Resistance	6 GOhms		
Safety Class	X1/Y2		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.