

GMA.0B.040.DG

SUMMARY

Wires



Image is for illustrative purpose only

| Series | OB |
|------------------|-------------------------|
| Termination type | No contacts / Accessory |
| IP rating | 0 |
| AWG wire size | 0.00 - 0.00 |
| Cable Ø | 4.00 - 4.40 mm |
| Status | active |

Download

Request a quote Catalog

TECHNICAL DETAILS

Mechanics


| Shell Style/Model | GMA*: Bend relief Grey |
|--|--|
| Keying | No keying |
| Housing Material | Thermoplastic polyurethane elastomer (Elastollan 1185 A) |
| Variant | G : Gray |
| Weight | .46 g |
| Performance Configuration Insulator Rated Current | G: PEEK/Pehd |

Others

Temp (min / max): -40°C / +80°C

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

DRAWINGS



No keying

Dimensions

| | А | L |
|-----|------|------|
| mm. | 4.0 | 24 |
| in. | 0,16 | 0,94 |

RECOMMENDED BY LEMO

Tools

Cables

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.